Product data sheet

Specifications



Canalis - distribution flexible length - 20 A - 24 m - 3 m between tap-offs

KDP20ED224300

(!) Discontinued

Main

Range Of Product	Canalis
Product Or Component Type	Busbar trunking
Product Compatibility	KDP
Busbar Description	Flexible bar

Complementary

Lighting Power socket distribution
230400 V
4 kV
690 V
20 A at 35 °C
0.34 kA
3.6 kA
50/60 Hz
2 pT
015 % 20 A 1533 % 16 A 33100 % 14 A
<0.72 V with power factor = 1 at 50 Hz with 1A for 100 m long <0.65 V with power factor = 0.9 at 50 Hz with 1A for 100 m long <0.58 V with power factor = 0.8 at 50 Hz with 1A for 100 m long <0.5 V with power factor = 0.7 at 50 Hz with 1A for 100 m long
L1 + N + PE
3000 mm
Spool
EN/IEC 61439-6 EN/IEC 60439-2
24 m
4.8 kg

Environment

Ip Degree Of Protection

IP55 conforming to IEC 60529

Ik Degree Of Protection	IK07 conforming to IEC 62262
Ambient Air Temperature For Operation	3540 °C (93 % of ln) 4045 °C (85 % of ln) 4550 °C (76 % of ln) 5055 °C (66 % of ln) 035 °C (100 % of ln)

Contractual warranty

Warranty

18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Eu Rohs Directive

Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration