

CANALIS KR 5X2500AL JUNCTION BLOCK / YA

KRA2500YA5

Main

Range	Canalis
Product Name	KR
Product Or Component Type	Electrical and mechanical jointing
Device Short Name	KRA
Range Compatibility	Canalis KR
Accessory / Separate Part Category	Connection accessory
Device Application	Jointing
Material	Aluminium
[le] Rated Operational Current	2500 A with aluminium
Polarity	3L + N + PE

Complementary

Housing Material	Mineral epoxy resin	
Contacts Material	Tinned aluminium	
[Ue] Rated Operational Voltage	1000 V	
Earth Conductor	Standard earth	
Mounting Location	Outdoor Indoor	
Mounting Support	Self-tapping screw	
Product Certifications	CE ATEX EAC	
Standards	IEC 61439-6	
Fixing Mode	By 2 bolts	
Tightening Torque	84 N.m	
Width	120 mm	
Height	270 mm	
Colour	Grey (RAL 7030)	
Quantity Per Set	Set of 1	

Environment

Ip Degree Of Protection	IP68 conforming to IEC 60529
Ik Degree Of Protection	IK10 conforming to IEC 62262

Pollution Degree 3

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	27.0 cm
Package 1 Width	12.0 cm
Package 1 Length	30.0 cm
Package 1 Weight	25.515 kg

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

⊘	Reach Free Of Svhc
⊘	Toxic Heavy Metal Free
⊘	Mercury Free
Ø	Rohs Exemption Information Yes
⊘	Halogen Free Product

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information