Product data sheet

Specifications



① Discontinued

Main

on mounting plate DOL starter -TeSys LC4-D - 12 A - coil 400 V AC

LC4D12AV7

() Discontinued on: Nov 30, 2021

Range Of Product	TeSys
Device Short Name	LC4
Product Or Component Type	DOL starter
Motor Power Kw	3 kW at 220230 V AC 50/60 Hz
	7.5 kW at 500 V AC 50/60 Hz
	5.5 kW at 380400 V AC 50/60 Hz
	5.5 kW at 415 V AC 50/60 Hz
	5.5 kW at 440 V AC 50/60 Hz
Utilisation Category	AC-3
[Ue] Rated Operational Voltage	400 V AC 50/60 Hz
[le] Rated Operational Current	16 A

Complementary

Device Composition	Fuse disconnector Contactor	
Mounting Support	Plate	
Width	86 mm	
Height	173 mm	
Depth	98 mm	
Net Weight	0.87 kg	

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	18.5 cm
Package 1 Width	11.5 cm
Package 1 Length	19 cm
Package 1 Weight	870 g

Contractual warranty

Warranty

18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc

Fa

Toxic Heavy Metal Free	
Mercury Free	
Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information