

TeSys LE - enclosed DOL reversing starter - 6 A - 400 V AC coil

LE2K065V7

Discontinued on: Dec 29, 2023

(!) Discontinued

Main

Range	TeSys
Product Name	TeSys LE
Device Short Name	LE2K
Product Or Component Type	Enclosed DOL reversing starter
Device Application	Standard
Utilisation Category	AC-3
Device Composition	Thermal overload relay ordered separately Reversing contactor
Motor Power Kw	3 kW at 440 V AC 50/60 Hz 1.5 kW at 220/230 V AC 50/60 Hz 2.2 kW at 380/400 V AC 50/60 Hz 2.2 kW at 415 V AC 50/60 Hz
[Ith] Conventional Free Air Thermal Current	6 A
[Uc] Control Circuit Voltage	400 V AC 50/60 Hz
Control Type	Push-button stop/reset red O Push-button start down arrow Push-button start up arrow

Complementary

Cable Entry Number	4 2 Pg 13 + 2 Pg 16 top 4 ISO20 top 4 2 Pg 13 + 2 Pg 16 bottom 4 ISO20 bottom
Width	175 mm
Height	165 mm
Depth	146 mm
Net Weight	1.08 kg

Environment

Material	Polycarbonate
Ip Degree Of Protection	IP65 conforming to IEC 60529
Ik Degree Of Protection	IK09 conforming to IEC 60529
Standards	IEC 60947-4-1
Ambient Air Temperature For Operation	-540 °C
Environmental Characteristic	Standard environment

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	24.9 cm
Package 1 Width	25.0 cm
Package 1 Length	25.0 cm
Package 1 Weight	1.62 kg

Contractual warranty

Warranty 18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



RoHS/REACh

Well-being performance

⊘	Reach Free Of Svhc	
⊘	Toxic Heavy Metal Free	
⊘	Mercury Free	
⊘	Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations