

TeSys LE - enclosed star-delta starter - 9 A - 400 V AC coil - no pushbuttons

LE3D09V7A04

Discontinued on: Nov 30, 2021

! Discontinued

Main

Range	TeSys	
Product Name	TeSys LE	
Device Short Name	LE3D	
Product Or Component Type	Enclosed star-delta starter	
Device Application	Standard	
Material	Polycarbonate	
Utilisation Category	AC-3	
Device Composition	Thermal overload relay ordered separately Star-delta contactors Mechanical interlock	
[le] Rated Operational Current	9 A AC-3	
Motor Power Kw	4 kW at 220 V AC 50/60 Hz 7.5 kW at 380/400 V AC 50/60 Hz 7.5 kW at 415 V AC 50/60 Hz 7.5 kW at 440 V AC 50/60 Hz	
[Uc] Control Circuit Voltage	400 V AC 50/60 Hz	
Control Type	Without	

Complementary

Connections - Terminals	Power circuit: screw clamp terminals	
	Control circuit: screw clamp terminals	
Cable Entry Number	2 ISO20 top	
	2 ISO25 top	
	2 ISO32 top	
	2 ISO40 top	
	2 ISO20 bottom	
	2 ISO25 bottom	
	2 ISO32 bottom	
	2 ISO40 bottom	
Width	186 mm	
Height	348 mm	
Depth	175.5 mm	
Net Weight 3.65 kg		

Environment

Ip Degree Of Protection	IP65 conforming to IEC 60529	
Ik Degree Of Protection	IK07 conforming to IEC 60529	

Standards	IEC 60947-4-1
Ambient Air Temperature For Operation	-540 °C
Environmental Characteristic	Standard environment
Product Certifications	UKCA

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	26 cm
Package 1 Width	29 cm
Package 1 Length	40 cm
Package 1 Weight	3.65 kg

Contractual warranty

Warranty 18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

Ø	Reach Free Of Svhc	
Ø	Toxic Heavy Metal Free	
⊘	Mercury Free	
Ø	Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information