

Product data sheet

Specifications



TeSys LE - enclosed DOL starter - 9 A - 380 V AC coil

LE4K095Q7

⚠ Discontinued on: Sep 27, 2020

⚠ Discontinued

Main

| | |
|---|--|
| Range | TeSys |
| Product Name | TeSys LE |
| Device Short Name | LE4K |
| Product Or Component Type | Enclosed DOL starter |
| Device Application | Standard |
| Material | Polycarbonate |
| Utilisation Category | AC-3 |
| Device Composition | Thermal overload relay ordered separately Contactor Fuse disconnecter |
| Motor Power Kw | 4 kW at 380/400 V AC 50/60 Hz 4 kW at 415 V AC 50/60 Hz 4 kW at 440 V AC 50/60 Hz 2.2 kW at 220/230 V AC 50/60 Hz |
| [Uc] Control Circuit Voltage | 380 V AC 50/60 Hz |
| [Ith] Conventional Free Air Thermal Current | 9 A |
| Associated Fuse Rating | 12 A 10 x 38 mm aM |
| Control Type | Push-button start green I Push-button stop/reset red O |

Complementary

| | |
|--------------------|--|
| Cable Entry Number | 4 ISO20 top 4 2 Pg 13 + 2 Pg 16 top 4 ISO20 bottom 4 2 Pg 13 + 2 Pg 16 bottom |
| Width | 175 mm |
| Height | 165 mm |
| Depth | 146 mm |
| Net Weight | 1.45 kg |

Environment

| | |
|---------------------------------------|------------------------------|
| Ip Degree Of Protection | IP65 conforming to IEC 60529 |
| Ik Degree Of Protection | IK09 conforming to IEC 60529 |
| Standards | IEC 60947-4-1 |
| Ambient Air Temperature For Operation | -5...40 °C |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|------------------------------|----------------------|
| Environmental Characteristic | Standard environment |
|------------------------------|----------------------|

Packing Units

| | |
|------------------------------|---------|
| Unit Type Of Package 1 | PCE |
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 17 cm |
| Package 1 Width | 18 cm |
| Package 1 Length | 24 cm |
| Package 1 Weight | 1.65 kg |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



RoHS/REACH

Well-being performance

✓ Reach Free Of Svhc

✓ Toxic Heavy Metal Free

✓ Mercury Free

✓ Rohs Exemption Information [Yes](#)

Certifications & Standards

Eu Rohs Directive Compliant
[EU RoHS Declaration](#)

China Rohs Regulation [China RoHS declaration](#)

Weee The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins