

Product data sheet

Specifications



Thermal overload relay, TeSys
Deca, 690VAC, 48 to 65A,
1NO+1NC, class 10A, EverLink
BTR screw

LRD365

Main

| | |
|-------------------------------------|---|
| Range | TeSys TeSys Deca |
| Product Name | TeSys LRD TeSys Deca |
| Product Or Component Type | Differential thermal overload relay |
| Device Short Name | LRD |
| Relay Application | Motor protection |
| Product Compatibility | LC1D65A LC1D50A |
| Network Type | DC AC |
| Thermal Overload Class | Class 10A conforming to IEC 60947-4-1 |
| Thermal Protection Adjustment Range | 48...65 A |
| [Ui] Rated Insulation Voltage | Power circuit: 600 V conforming to CSA Power circuit: 600 V conforming to UL Power circuit: 690 V conforming to IEC 60947-4-1 |

Complementary

| | |
|---|--|
| Network Frequency | 0...400 Hz |
| Mounting Support | Plate, with specific accessories Rail, with specific accessories Under contactor |
| Tripping Threshold | 1.14 +/- 0.06 Ir conforming to IEC 60947-4-1 |
| Auxiliary Contact Composition | 1 NO + 1 NC |
| [Ith] Conventional Free Air Thermal Current | 5 A for signalling circuit |
| Permissible Current | 0.95 A at 380 V AC-15 for signalling circuit 0.06 A at 440 V DC-13 for signalling circuit |
| [Ue] Rated Operational Voltage | 690 V AC 0...400 Hz for power circuit conforming to IEC 60947-4-1 |
| Associated Fuse Rating | 4 A gG for signalling circuit 4 A BS for signalling circuit |
| [Uimp] Rated Impulse Withstand Voltage | 6 kV |
| Phase Failure Sensitivity | Tripping current 130 % of Ir on two phase, the last one at 0 |
| Control Type | Red push-button: stop Blue push-button: reset |
| Temperature Compensation | -20...60 °C |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|-------------------------|---|
| Connections - Terminals | Control circuit: screw clamp terminals 2 cable(s) 1...2.5 mm² flexible without cable end Control circuit: screw clamp terminals 2 cable(s) 1...2.5 mm² flexible with cable end Control circuit: screw clamp terminals 2 cable(s) 1...2.5 mm² solid without cable end Power circuit: EverLink BTR screw connectors 1 cable(s) 1...35 mm² flexible without cable end Power circuit: EverLink BTR screw connectors 1 cable(s) 1...35 mm² flexible with cable end Power circuit: EverLink BTR screw connectors 1 cable(s) 1...35 mm² solid without cable end |
| Tightening Torque | Control circuit: 1.7 N.m - on screw clamp terminals Power circuit: 5 N.m - on EverLink BTR screw connectors |
| Height | 70 mm |
| Width | 55 mm |
| Depth | 123 mm |
| Net Weight | 0.375 kg |

Environment

| | |
|---------------------------------------|--|
| Climatic Withstand | conforming to IACS E10 |
| Ip Degree Of Protection | IP20 conforming to IEC 60529 |
| Ambient Air Temperature For Operation | -20...60 °C without derating conforming to IEC 60947-4-1 |
| Ambient Air Temperature For Storage | -60...70 °C |
| Flame Retardance | V1 conforming to UL 94 |
| Mechanical Robustness | Shocks: 15 Gn for 11 ms conforming to IEC 60068-2-7 Vibrations: 4 gn conforming to IEC 60068-2-6 |
| Dielectric Strength | 1.89 kV at 50 Hz conforming to IEC 60947-1 |
| Standards | EN/IEC 60947-4-1 EN/IEC 60947-5-1 UL 60947-4-1 UL 60947-5-1 CSA C22.2 No 60947-4-1 CSA C22.2 No 60947-5-1 GB/T 14048.4 GB/T 14048.5 EN 50495 |
| Product Certifications | IEC UL CSA CCC EAC DNV-GL RMRS EU-RO MR LROS (Lloyds register of shipping) ATEX INERIS UKCA |

Packing Units

| | |
|------------------------------|-----------|
| Unit Type Of Package 1 | PCE |
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 6.200 cm |
| Package 1 Width | 11.000 cm |
| Package 1 Length | 14.000 cm |
| Package 1 Weight | 394.000 g |
| Unit Type Of Package 2 | S02 |

| | |
|------------------------------|-----------|
| Number Of Units In Package 2 | 13 |
| Package 2 Height | 15.000 cm |
| Package 2 Width | 30.000 cm |
| Package 2 Length | 40.000 cm |
| Package 2 Weight | 5.453 kg |
| Unit Type Of Package 3 | P06 |
| Number Of Units In Package 3 | 208 |
| Package 3 Height | 75.000 cm |
| Package 3 Width | 60.000 cm |
| Package 3 Length | 80.000 cm |
| Package 3 Weight | 97.732 kg |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

✓ Reach Free Of Svhc

✓ Toxic Heavy Metal Free

✓ Mercury Free

✓ Rohs Exemption Information Yes

Certifications & Standards

| | |
|---------------------------|---|
| Reach Regulation | REACH Declaration |
| Eu Rohs Directive | Compliant EU RoHS Declaration |
| China Rohs Regulation | China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope) |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End of Life Information |
| California Proposition 65 | WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov |