# Product data sheet

Specifications



# plug in base, ComPact NSX100/160/250, front/rear connected, 4 poles

LV429267

#### Main

Product Or Component Type	Plug-in base
Accessory / Separate Part Category	Mounting accessory
Range Compatibility	ComPact ComPact NSX100
	ComPact ComPact NSX160
	ComPact ComPact NSX250
	ComPact Compact NSX100 DC
	ComPact Compact NSX160 DC
	ComPact Compact NSX250 DC
Poles Description	4P

## Complementary

Mounting Mode	Plug-in
[In] Rated Current	250 A
Earth-Leakage Protection	Without

## **Packing Units**

J	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	9.400 cm
Package 1 Width	14.800 cm
Package 1 Length	22.400 cm
Package 1 Weight	1.152 kg
Unit Type Of Package 2	S04
Number Of Units In Package 2	14
Package 2 Height	30.000 cm
Package 2 Width	40.000 cm
Package 2 Length	60.000 cm
Package 2 Weight	16.894 kg
Unit Type Of Package 3	P12
Number Of Units In Package 3	56
Package 3 Height	50.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	78.904 kg

# **Contractual warranty**

Warranty

18 months

### Sustainability

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Eq

Transparency RoHS/REACh

#### Well-being performance



#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations