

# Product data sheet

Specifications



## TeSys F - contactor coil - LX1FX - 200...208 V AC 40...400 Hz

LX1FX200

### Main

Range	TeSys
Product Or Component Type	Contactor coil
Device Short Name	LX1FX
Range Compatibility	TeSys TeSys F LC1F contactor
Product Compatibility	LC1F780
Control Circuit Type	AC at 40...400 Hz
[Uc] Control Circuit Voltage	200...208 V AC 40...400 Hz
Inductance Of Closed Circuit	0.66 H
Average Resistance	15.5 Ohm inrush at 20 °C 750 Ohm holding at 20 °C
Operating Time	130...230 ms opening 40...80 ms closing
Mechanical Durability	5 Mcycles
Maximum Operating Rate	600 cyc/h 55 °C

### Complementary

Coil Technology	Without built-in suppressor module
Control Circuit Voltage Limits	Operational: 0.85...1.1 Uc 40...400 Hz (at 55 °C) Drop-out: 0.2...0.4 Uc 40...400 Hz (at 55 °C)
Inrush Power In Va	2100 VA 40...400 Hz cos phi 0.9 (at 20 °C)
Hold-In Power Consumption In Va	50 VA 40...400 Hz cos phi 0.3 (at 20 °C)
Heat Dissipation	44 W at 40...400 Hz

### Environment

Ambient Air Temperature For Operation	-5...55 °C
Net Weight	3 kg
Quantity Per Set	Set of 2

### Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	13.5 cm
Package 1 Width	18.0 cm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 1 Length	23.5 cm
Package 1 Weight	3.0 kg

## Contractual warranty

Warranty	18 months
----------	-----------

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency   RoHS/REACH

## Well-being performance

✓ Reach Free Of Svhc

✓ Toxic Heavy Metal Free

✓ Mercury Free

✓ Rohs Exemption Information   [Yes](#)

## Certifications & Standards

Reach Regulation	<a href="#">REACH Declaration</a>
Eu Rohs Directive	Compliant <a href="#">EU RoHS Declaration</a>
China Rohs Regulation	<a href="#">China RoHS declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>