

TeSys F - specific contactor coil - 240 V AC 40...400 Hz low consumption

LX9FH2402

Discontinued on: Sep 18, 2020

① Discontinued

Main

Range	TeSys
Product Or Component Type	Specific contactor coil
Device Short Name	LX9FH
Range Compatibility	TeSys TeSys F LC1F contactor
Product Compatibility	LC1F265 LC1F330
Control Circuit Type	AC at 40400 Hz low consumption
[Uc] Control Circuit Voltage	240 V AC 40400 Hz
Average Resistance	1968 Ohm holding at 20 °C 88 Ohm inrush at 20 °C
Operating Time	25 ms opening 45 ms closing
Mechanical Durability	10 Mcycles
Maximum Operating Rate	3600 cyc/h 55 °C

Complementary

Coil Technology	Without built-in suppressor module
Control Circuit Voltage Limits	Operational: 0.851.1 Uc (at 55 °C) Drop-out: 0.350.55 Uc (at 55 °C)
Inrush Power In Va	560660 VA 40400 Hz (at 20 °C)
Hold-In Power Consumption In Va	810 VA 40400 Hz (at 20 °C)
Heat Dissipation	8.410.4 W

Environment

Ambient Air Temperature For Operation	-555 °C
Net Weight	0.75 kg

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	9.5 cm
Package 1 Width	10.5 cm
Package 1 Length	19 cm

Package 1 Weight 882 g

Contractual warranty

Warranty 18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Well-being performance

	Reach Free Of Svhc	
	Toxic Heavy Metal Free	
	Mercury Free	
	Rohs Exemption Information	Yes
Eu Rohs Directive		Pro-active compliance (Product out of EU RoHS legal scope)
		EU RoHS Declaration
Chir	na Rohs Regulation	China RoHS declaration