# Product data sheet

Specifications



① Discontinued

## ION7650, wDispl, 10MB 1024s, 1A 240VAC/300VDC 60Hz -RS+T2+E+F - 8I+3R+4O

M7650B1E0B6F1A0A

Uiscontinued on: Jun 1, 2021

#### Main

Range	PowerLogic
Device Short Name	ION7650
Product Or Component Type	Energy and power quality meter

### Complementary

Complementary	
Power Quality Analysis	harmonic distortion voltage sag and swell detection waveform capture compliance monitoring dip and swell, transient disturbance direction detection programmablity (logic and math functions) setpoint learning up to the 63rd harmonic
Device Application	Energy pulsing and totalisation Load curtailment Equipment monitoring and control Co-generation and IPP monitoring Tariff metering Instrument transformer correction Demand and power factor control
Type Of Measurement	Current Voltage Frequency Apparent power total Power factor total Apparent power per phase Power factor per phase Active power total Active power total Reactive power total Reactive power per phase
Supply Voltage	110300 V DC 85240 V AC 4763 Hz
Network Frequency	60 Hz
[In] Rated Current	1 A
Type Of Network	1P + N 3P 3P + N
Power Consumption In Va	20 VA
Maximum Power Consumption In Va	45 VA
Display Resolution	320 x 240 pixels QVGA
Display Type	Backlit LCD

Sampling Rate	1024 samples/cycle
Measurement Current	01 A
Input Type	Current 0.00520 A (impedance 0.015 Ohm)
Measurement Voltage	100600 V AC phase to phase 57347 V AC phase to neutral
Frequency Measurement Range	4269 Hz
Number Of Inputs	8 digital 120 V DC
Measurement Accuracy	Current 0.1 % 15 A Voltage 0.1 % 57288 V Energy 0.2 %
Accuracy Class	Class 0.2S energy conforming to IEC 62053-22
Number Of Outputs	3 relay 4 solid state
Communication Port Protocol	Telnet DNP3 at <= 115.2 kbits/s ION at <= 115.2 kbits/s Modbus at <= 115.2 kbits/s IEC 61850 TCP/IP at 10/100 Mbit/s
Communication Port Support	RS485 Infrared SUB-D 9: RS232 SC: fiber optic
Data Recording	Data logs Trending/forecasting Min/max of instantaneous values Event logs GPS synchronisation Time stamping Sequence of event recording
Transmission Rate	<= 115.2 kbits/s 10/100 Mbit/s
Memory Capacity	10 MB
Web Services	Web server
Tamperproof Of Settings	Protected by access code
Compatibility Code	ION7650

#### Environment

Electromagnetic Compatibility	Electrical fast transient/burst immunity test conforming to IEC 61000-4-4 Electrostatic discharge conforming to IEC 61000-4-2 Susceptibility to electromagnetic fields conforming to IEC 61000-4-3 1.2/50 µs shock waves immunity test conforming to IEC 61000-4-5 Conducted and radiated emissions B conforming to CISPR 22
Mounting Mode	Flush-mounted
Mounting Support	Enclosure door
Type Of Installation	Indoor installation
Overvoltage Category	III
Ip Degree Of Protection	IP30 back: conforming to IEC 60529 IP50 front face: conforming to IEC 60529
Relative Humidity	595 %
Pollution Degree	2
Ambient Air Temperature For	-2070 °C

Ambient Air Temperature For Storage	-4085 °C
Operating Altitude	02000 m
Standards	IEC 61010-1
Width	192 mm
Depth	174 mm
Height	192 mm
Net Weight	1.9 kg

## **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	26 cm
Package 1 Width	28 cm
Package 1 Length	44 cm
Package 1 Weight	3.5 kg

#### **Sustainability**

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
California Proposition 65	WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov