Product data sheet

Specifications



current transformer tropicalised DIN mount 400 5 for bars 10x40 20x32 25x25

METSECT5MC040

Main

Range	PowerLogic
Product Name	СТ
Product Or Component Type	Current transformer
Secondary Current	5 A
Accuracy Class	Class 0.5 at 8 VA Class 1 at 10 VA
[In] Rated Current	400 A

Complementary

Compromontary	
Current Transformer Type	Tropicalised for busbar and cable
Current Transformer Ratio	400/5
[Ith] Conventional Free Air Thermal Current	24 kA
Dynamic Withstand Current	2.5 lth
Maximum Safety Factor	5
[Ue] Rated Operational Voltage	< 720 V AC 50/60 Hz
[Ui] Rated Insulation Voltage	3 kV
Mounting Mode	Insulated locking screw Clip-on By screws
Mounting Support	Busbar DIN rail Mounting plate
Width	Outside: 70 mm Inner: 41 mm
Height	Outside: 95 mm Inner: 41 mm
Depth	Frame : 45 mm Total : 65 mm
Diameter	32 mm
Net Weight	0.404 kg
[Uimp] Rated Impulse Withstand Voltage	3 kV
Electrical Insulation Class	Class B
Cable Outer Diameter	32 mm
Opening Of Bars	25.5 x 25.5 40.5 x 10.5 32.5 x 20.5

Sealing

Without

Environment

Standards	VDE 0414 IEC 61869-2
Product Certifications	EAC CE
Ip Degree Of Protection	IP20
Relative Humidity	095 %
Ambient Air Temperature For Operation	-2560 °C

Packing Units

-	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	9.000 cm
Package 1 Width	7.300 cm
Package 1 Length	12.000 cm
Package 1 Weight	400.000 g
Unit Type Of Package 2	S03
Number Of Units In Package 2	25
Package 2 Height	30.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	10.440 kg

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Yes

Learn more about Green Premium >

Guide to assess a product's sustainability >



RoHS/REACh

Well-being performance



Rohs Exemption Information

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins