

LVCT - 3-in-1 solid core CT RJ45 - 35mm entraxe - 160A : 0.333V output

METSECTV35016

Main

Range	PowerLogic	
Product Or Component Type	Current transformer	
Accessory / Separate Part Category	Measurement accessory	
Range Compatibility	EasyLogic EasyLogic PM2200 PM2210R EasyLogic EasyLogic PM2200 PM2220R PowerLogic PowerLogic PM5000 PM5310R PowerLogic PowerLogic PM5000 PM5320R	
Current Transformer Type	Triple solid core	
Output Voltage	0.333 V	

Complementary

[In] Rated Current	160 A
Network Frequency	50 Hz 60 Hz
Measurement Accuracy	+/- 0.5 %
Width	105 mm
Height	80 mm
Depth	38 mm body: 54 mm total:
Distance Between Centers	35 mm
Opening Of Bars	25 x 21
Net Weight	550 g

Environment

Standards	EN 60044-8 EN 61869-2	
Product Certifications	CE	
	UI	

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	7.000 cm
Package 1 Width	10.000 cm
Package 1 Length	13.000 cm

Package 1 Weight	402.000 g
Unit Type Of Package 2	S03
Number Of Units In Package 2	27
Package 2 Height	30.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	11.195 ka

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Well-being performance

Well-being performance		
Reach Free Of Svhc		
Rohs Exemption Information	Yes	
Reach Regulation	REACh Declaration	
Eu Rohs Directive	Compliant EU RoHS Declaration	
China Rohs Regulation	China RoHS declaration	
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	