

Unica - 1 RJ45 socket (S-One) - 2 m - Cat.5e, UTP - ivory

MGU5.421.25ZD

Discontinued on: Jun 15, 2023

(!) Discontinued

Main

| Range | Unica |
|---------------------------|------------------------------------|
| Aesthetic Name | Unica (standard aesthetic) |
| Product Or Component Type | Data socket |
| Device Application | Communication |
| Device Presentation | Mechanism with fixing frame |
| Colour Tint | lvory |
| Data Socket Type | RJ45 4 contact(s) Cat.5e < 155 MHz |
| Provided Equipment | Protective flap Label holder |

Complementary

| J | |
|-----------------------------|--|
| Communication Network Type | 1000BASE-T |
| Communication Port Protocol | ATM 155 Mbps |
| Number Of Modules | 2 modules |
| Socket Number | 1 |
| Type Of Footprint | Infraplus |
| Connector Type | S-One |
| Cable Shielding Type | U/UTP |
| Organization Of Wire | Unshielded twisted pair |
| Connections - Terminals | Click |
| Marking | Colour coding |
| Device Mounting | Flush |
| Fixing Mode | Screws By screw: shield |
| Installation Direction | Straight |
| Material | ASA + PC: mechanism cover Zamak: fixing frame |
| Depth | 36 mm |
| Width | 70.9 mm |
| Height | 70.9 mm |
| Embedding Depth | 25 mm |
| Net Weight | 0.051 kg |

Environment

| Ip Degree Of Protection | IP40 |
|---------------------------------------|--|
| Ik Degree Of Protection | IK01 |
| Ambient Air Temperature For Operation | 1530 °C |
| Ambient Air Temperature For Storage | 035 °C |
| Environmental Characteristic | Petrol Window-cleaning fluid Alcohol Oil Bleach Acetone UV resistant Liquid soap |
| Standards | ISO 8877 |

Packing Units

| Unit Type Of Package 1 | PCE |
|------------------------------|----------|
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 4.0 cm |
| Package 1 Width | 7.5 cm |
| Package 1 Length | 7.5 cm |
| Package 1 Weight | 48.0 g |
| Unit Type Of Package 2 | BB1 |
| Number Of Units In Package 2 | 10 |
| Package 2 Height | 8.0 cm |
| Package 2 Width | 20.0 cm |
| Package 2 Length | 22.5 cm |
| Package 2 Weight | 588.0 g |
| Unit Type Of Package 3 | \$03 |
| Number Of Units In Package 3 | 50 |
| Package 3 Height | 30.0 cm |
| Package 3 Width | 30.0 cm |
| Package 3 Length | 40.0 cm |
| Package 3 Weight | 3.312 kg |
| Package 3 Weight | 3.312 kg |

Contractual warranty

Warranty 18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

| Eu Rohs Directive | Under investigation |
|---------------------|--|
| Circularity Profile | No need of specific recycling operations |