

# Product data sheet

Specifications



## PLA door 750x750

NSYDPLA77G

### Main

Range	Thalassa
Accessory / Separate Part Category	Enclosure accessory
Product Or Component Type	Door
Application	Multi-purpose
For Enclosure Nominal Dimensions	-
Mounting Location	Front
Range Compatibility	Thalassa Thalassa PLA
Device Composition	1 door locking system
Quantity Per Set	Set of 1

### Complementary

Material	Door: polyester reinforced with fibreglass
Colour	Door: grey (RAL 7035)
Lock Type	Lock 5 mm double bar
Number Of Locks	1
Door Type	Plain
Door Opening Side	Reversible (120 °) Reversible (180 °)
Maximum Load	30 kg/m²
Height	750 mm
Width	750 mm

### Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	79.0 cm
Package 1 Width	6.0 cm
Package 1 Length	80.0 cm
Package 1 Weight	5.85 kg

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency   RoHS/REACH

## Well-being performance

✓ Mercury Free

✓ Rohs Exemption Information   [Yes](#)

## Certifications & Standards

Reach Regulation	<a href="#">REACH Declaration</a>
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations