Specifications



# Glazed door for Spacial S3D H800xW800 RAL 7035, with lock

NSYDS3D88T

## Main

Range	Spacial
Accessory / Separate Part Category	Enclosure accessory
Product Or Component Type	Door
Application	Multi-purpose
For Enclosure Nominal Dimensions	-
Mounting Location	Front
Range Compatibility	Spacial Spacial S3D
Device Composition	1 door locking system
Quantity Per Set	Set of 1

### Complementary

J	
Material	Door: sheet steel
Colour	Grey (RAL 7035)
Surface Finish	Textured epoxy polyester
Lock Type	Lock 3 mm double bar
Number Of Locks	1
Door Type	Glazed
Door Opening Side	Reversible (120 °)
Height	800 mm nominal:
Width	800 mm nominal:
Net Weight	7.92 kg

## **Packing Units**

•	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	5.0 cm
Package 1 Width	81.0 cm
Package 1 Length	82.0 cm
Package 1 Weight	9.508 kg
Unit Type Of Package 2	РАМ
Number Of Units In Package 2	10

Package 2 Height	66.0 cm
Package 2 Width	100.0 cm
Package 2 Length	120.0 cm
Package 2 Weight	108.0 kg

## **Contractual warranty**

Warranty

18 months

### **Sustainability**

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

#### Well-being performance

Mercury Free	
Rohs Exemption Information	Yes
Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration
	Product out of China RoHS scope. Substance declaration for your information