Specifications

0

Earth leads section 6mm², length 160mm, eyelet hole 6,4mm. Packaging unit: 10.

NSYEL166D6

Main

Range	Spacial
Anwendung	Multi-purpose
Product Or Component Type	Earthing wire
Device Composition	1 lead
Quantity Per Set	Set of 10

Complementary

Material	PVC (polyvinyl chloride) green and yellow for sheath Brass and copper alloy for terminal	
Fixing Mode	Nut and washer - on earth connection location	
Length	160 mm	
Width	10 mm	
Nominal Cross Section	6 mm ²	
Diameter	6.4 mm	

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	1 cm
Package 1 Width	10.5 cm
Package 1 Length	20 cm
Package 1 Weight	13 g
Unit Type Of Package 2	BB1
Number Of Units In Package 2	10
Package 2 Height	20 cm
Package 2 Width	10.5 cm
Package 2 Length	1 cm
Package 2 Weight	134 g
Unit Type Of Package 3	P12
Number Of Units In Package 3	9600
Package 3 Height	56 cm
Package 3 Width	80 cm

Package 3 Length	120 cm
Package 3 Weight	152.1 kg

Contractual warranty

Warranty

18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Eq

Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc
Toxic Heavy Metal Free

Mercury Free

Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations