

# Product data sheet

Specifications

## Locking system for SFX 2000mm

NSYLSSF20



### Main

Range	Spacial
Product Or Component Type	Locking system

### Complementary

Accessory / Separate Part Category	Locking accessory
Accessory / Separate Part Type	Locking system
Device Application	Multi-purpose
Mounting Support	Direct mounting on door
Range Compatibility	Spacial Spacial SMX Spacial Spacial SFX
Device Composition	1 shape insert 1 key 1 cam 1 handle 1 locking bar 1 fixing elements
Quantity Per Set	Set of 1
Material	Handle: zamak
Net Weight	1.2 kg
Lock Type	3 points lock, 5 mm double-bar

### Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	8.0 cm
Package 1 Width	8.0 cm
Package 1 Length	86.0 cm
Package 1 Weight	1.2 kg

### Contractual warranty

Warranty	18 months
----------	-----------

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

# Sustainability

**Green Premium™ label** is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)



Transparency   RoHS/REACH

## Well-being performance

✓ Mercury Free

✓ Rohs Exemption Information   [Yes](#)

## Certifications & Standards

Reach Regulation	<a href="#">REACH Declaration</a>
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations