



Floor standing polyester enclosure, Thalassa PLA, plain door, completely sealed, 1250x750x620mm, IP65, IK10

NSYPLA1276G

### Main

| Range                     | Thalassa   |
|---------------------------|--|
| Product Name              | Thalassa PLA   |
| Enclosure Type            | Multi-purpose  |
| Product Or Component Type | Suitable enclosure                                       |
| Version                   | PLA  |
| Nominal Height            | 1250 mm  |
| Nominal Width             | 750 mm   |
| Nominal Depth             | 620 mm   |
| Enclosure Mounting        | Floor-standing   |
| Device Composition        | 1 top part 1 bottom part 2 side part 1 rear panel 1 door |

# Complementary

| Body Type                   | Sealed top and bottom part assembled with side parts                      |
|-----------------------------|---|
| Door Type                   | Plain front   |
| Number Of Doors             | 1 door(s)   |
| Door Opening Side           | Reversible (120 °)  |
| Lock Type                   | 4 points lock, 5 mm double-bar  |
| Accessibility For Operation | Front<br>Rear   |
| Removable Parts             | Door by hinges<br>Rear panel by fixing element                            |
| Material                    | Polyester reinforced with fibreglass                                      |
| Colour                      | Grey (RAL 7035)   |
| Standards                   | IEC 62208<br>UL 508 A   |
| Nema Degree Of Protection   | NEMA 3 NEMA 3S NEMA 2 NEMA 5 NEMA 5 NEMA 3R NEMA 3X NEMA 12 NEMA 1 NEMA 1 |

| Product Certifications      | Veritas UL/cUL listed DNV Marine |
|-----------------------------|----------------------------------|
| Electrical Insulation Class | Class II                         |

# **Environment**

| Ip Degree Of Protection             | IP65 conforming to IEC 60529 (completely sealed) |
|-------------------------------------|--|
| Ik Degree Of Protection             | IK10 conforming to IEC 62262 (plain door)        |
| Fire Resistance                     | 960 °C conforming to IEC 62208                   |
| Ambient Air Temperature For Storage | -3590 °C   |

# **Packing Units**

| Unit Type Of Package 1       | PCE      |
|------------------------------|----------|
| Number Of Units In Package 1 | 1        |
| Package 1 Height             | 126.0 cm |
| Package 1 Width              | 78.0 cm  |
| Package 1 Length             | 65.0 cm  |
| Package 1 Weight             | 45.0 kg  |

## Sustainability

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

## Well-being performance



Mercury Free



Rohs Exemption Information

Yes

#### **Certifications & Standards**

| Reach Regulation         | REACh Declaration   |
|--------------------------|---|
| Eu Rohs Directive        | Pro-active compliance (Product out of EU RoHS legal scope)  |
| China Rohs Regulation    | China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile   |
| Circularity Profile      | No need of specific recycling operations  |
|                          |   |