

Floor standing polyester enclosure, Thalassa PLA, plain door, ventilated canopy, 1000x750x320mm, IP44, IK10

NSYPLAT1073G

### Main

| Thalassa  |
|---|
| Thalassa PLA  |
| Multi-purpose   |
| Suitable enclosure  |
| PLAT  |
| 1000 mm   |
| 750 mm  |
| 320 mm  |
| Floor-standing  |
| 1 top part 1 bottom part 2 side part 1 rear panel 1 door 1 canopy |
|   |

# Complementary

| Body Type                   | Open top and sealed bottom part assembled with side parts                  |
|-----------------------------|--|
| Door Type                   | Plain front  |
| Number Of Doors             | 1 door(s)  |
| Door Opening Side           | Reversible (120 °)   |
| Lock Type                   | 4 points lock, handle with 5 mm double bar insert                          |
| Accessibility For Operation | Front<br>Rear<br>Top   |
| Removable Parts             | Door by hinges<br>Rear panel by fixing element<br>Canopy by fixing element |
| Material                    | Polyester reinforced with fibreglass                                       |
| Colour                      | Grey (RAL 7035)  |
| Standards                   | IEC 62208  |
| Product Certifications      | Veritas  |
| Electrical Insulation Class | Class II   |

#### **Environment**

**Ip Degree Of Protection** IP44 conforming to IEC 60529 (with ventilated canopy)

| Ik Degree Of Protection             | IK10 conforming to IEC 62262 (plain door) |
|-------------------------------------|---|
| Fire Resistance                     | 960 °C conforming to IEC 62208            |
| Ambient Air Temperature For Storage | -3590 °C                                  |

# **Packing Units**

| Unit Type Of Package 1       | PCE      |
|------------------------------|----------|
| Number Of Units In Package 1 | 1        |
| Package 1 Height             | 101.0 cm |
| Package 1 Width              | 78.0 cm  |
| Package 1 Length             | 38.0 cm  |
| Package 1 Weight             | 29.83 kg |
| Unit Type Of Package 2       | PAM      |
| Number Of Units In Package 2 | 3        |
| Package 2 Height             | 120 cm   |
| Package 2 Width              | 100 cm   |
| Package 2 Length             | 119 cm   |
| Package 2 Weight             | 101 kg   |

# Sustainability

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

### Well-being performance



Mercury Free



Rohs Exemption Information

Yes

### **Certifications & Standards**

| Reach Regulation         | REACh Declaration   |
|--------------------------|---|
| Eu Rohs Directive        | Pro-active compliance (Product out of EU RoHS legal scope)  |
| China Rohs Regulation    | China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile   |
| Circularity Profile      | No need of specific recycling operations  |
|                          |   |