

Product data sheet

Specifications



adaptor plates for vers.PLAZorZT
D420mm 1 door mounting
NSYPAPL/DPLA/DLP/BRF/BRP

NSYPTZ4

Main

Category	Mounting accessory
Product Or Component Type	Adapter plate
Range Compatibility	Thalassa Thalassa PLA Thalassa Thalassa PHD
Application	Multi-purpose
Nominal Dimensions Of The Housing	- D: 420 mm
Mounting Location	Enclosure bottom
Device Composition	2 plate fixing elements
Material	Galvanised steel

Complementary

Fixing Mode	Screw and insert - screw type M8 - bottom of enclosure location
Height	80 mm
Width	15 mm
Depth	420 mm real:

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	8.0 cm
Package 1 Width	1.5 cm
Package 1 Length	30.0 cm
Package 1 Weight	930.0 g

Contractual warranty

Warranty	18 months
----------	-----------

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Sustainability

Green Premium™ label is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)



Transparency RoHS/REACH

Well-being performance

✓ Reach Free Of Svhc

✓ Toxic Heavy Metal Free

✓ Mercury Free

✓ Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation	REACH Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations