

# Spacial S3HF H700xW500xD250 EMC-immunity IP55 RAL7035

NSYS3HF7525P

(!) Discontinued

#### Main

Range	Spacial
Product Name	Spacial S3HF
Application	Industrial application
Category	Compact enclosure
Enclosure Nominal Height	700 mm
Enclosure Nominal Width	500 mm
Enclosure Nominal Depth	250 mm
Door Type	Plain
Mounting Plate Description	Without mounting plate
Type Of Gland Plate	Without gland plate
Installation Accessory Type	Wall-mounting
Device Composition	1 body 1 door with lock 1 mounting plate

# Complementary

Body Type	Single piece body
Number Of Doors	Front face: 1 door(s)
Lock Type	3 points lock, 3 mm double-bar
Accessibility For Operation	Front
Removable Parts	Door by hinges
Material	Body: aluzinc
Surface Finish	Epoxy-polyester powder
Colour	Grey (RAL 7035)
Standards	IEC 60529
Net Weight	23.5 kg

### **Environment**

Electromagnetic Compatibility	EMC immunity
Ik Degree Of Protection	IK10 conforming to IEC 62262
Ip Degree Of Protection	IP55

# **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	70 cm
Package 1 Width	50 cm
Package 1 Length	25 cm
Package 1 Weight	23.5 kg

## Sustainability

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

## Well-being performance



#### **Certifications & Standards**

Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile