

# Set of 2 uprights for mount. hor.support plate or 19"chassis in PLAencl.H750mm

NSYSPLA75

#### Main

Range	Thalassa
Accessory / Separate Part Category	Mounting accessory
Product Or Component Type	Upright
Device Application	Multi-purpose
<b>Enclosure Nominal Dimensions</b>	- H: 750 mm D: 320 mm - H: 750 mm D: 420 mm
Mounting Support	Intermediate support in the 2-door enclosures
Range Compatibility	Thalassa Thalassa PLA
Device Composition	fixing elements 1 right upright 1 left upright
Material	Galvanised steel

### Complementary

Fixing Mode	By fixing element - sides of enclosure location	
Adjustment	Adjustable in depth every 50 mm with caged nuts	
Height	750 mm nominal:	
Depth	70 mm	
Cut-Out Dimensions	11 x 13 mm	

## **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	2.0 cm
Package 1 Width	58.0 cm
Package 1 Length	7.0 cm
Package 1 Weight	200.0 g

#### **Contractual warranty**

Warranty 18 months

#### **Sustainability**

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

#### Well-being performance

✓ Reach Free Of Svhc
 ✓ Toxic Heavy Metal Free
 ✓ Mercury Free
 ✓ Rohs Exemption Information

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration  Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations