Specifications



ABS box IP66 IK07 RAL7035 Int.H105W105D55 Ext.H116W116D62 Opaque cover H10

NSYTBS11116

Main

| mann | |
|---------------------|----------------------------------------|
| Range | Thalassa |
| Product Name | Thalassa TBS |
| Device Application | Multi-purpose |
| Category | Industrial box |
| Height | 116 mm |
| Width | 116 mm |
| Depth | 62 mm |
| Internal Height | 105 mm |
| Internal Width | 105 mm |
| Internal Depth | 55 mm |
| Enclosure Mounting | Wall mounted |
| Device Composition | 1 body 1 cover 4 cover screw |
| Quantity Per Set | Set of 5 |
| Body Type | One piece moulded |
| Type Of Front Cover | Low plain cover |
| Cover Fixing | Plastic screws |
| Lock Type | Captive screw flat outside sealed area |
| Removable Parts | Cover by captive screws |

Complementary

| Material | ABS (acrylonitrile butadiene-styrene) |
|----------------------------------------|---------------------------------------|
| Colour | Grey (RAL 7035) |
| Standards | IEC 62208 |
| Product Certifications | ΤÜV |
| Electrical Insulation Class | Class II |
| Ip Degree Of Protection | IP66 conforming to NEMA 4.4X |
| Ik Degree Of Protection | IK07 conforming to IEC 62262 |
| Glow Wire Resistance | 650 °C conforming to IEC 60695-2-11 |
| Ambient Air Temperature For Storage | -1540 °C |
| Operating Temperature | -2560 °C |

| Net | Weight |
|-----|--------|
|-----|--------|

0.151 kg

| i acting child | |
|------------------------------|-----------|
| Unit Type Of Package 1 | PCE |
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 6.1 cm |
| Package 1 Width | 11.6 cm |
| Package 1 Length | 11.5 cm |
| Package 1 Weight | 130 g |
| Unit Type Of Package 2 | BB1 |
| Number Of Units In Package 2 | 5 |
| Package 2 Height | 12.4 cm |
| Package 2 Width | 12.4 cm |
| Package 2 Length | 32.8 cm |
| Package 2 Weight | 742 g |
| Unit Type Of Package 3 | CAR |
| Number Of Units In Package 3 | 75 |
| Package 3 Height | 40.2 cm |
| Package 3 Width | 40 cm |
| Package 3 Length | 59.6 cm |
| Package 3 Weight | 11.954 kg |
| | |

Contractual warranty

Warranty

18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc

Toxic Heavy Metal Free

Mercury Free

Eq

Rohs Exemption Information Yes

Certifications & Standards

| Reach Regulation | REACh Declaration |
|--------------------------|---------------------------------------------------------------------------------------------|
| Eu Rohs Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| China Rohs Regulation | China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope) |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |