



# Polyester glassreinf. plinth for encl. PLA(T)103 front opening IP44-IK10 RAL7035

NSYZA2103G

#### Main

Range	Thalassa
Accessory / Separate Part Category	Enclosure accessory
Product Or Component Type	Plinth
Application	Multi-purpose
Nominal Dimensions Of The Housing	-
Device Composition	fixing elements 2 front panel 2 side part
Range Compatibility	Thalassa Thalassa PLA

# Complementary

Fixing Mode	By screws - on side parts location
Colour	Plinth: grey (RAL 7035)
Height	200 mm
Width	994 mm
Depth	250 mm

#### **Environment**

Ip Degree Of Protection	IP44
Ik Degree Of Protection	IK10

## **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	16.0 cm
Package 1 Width	21.0 cm
Package 1 Length	102.0 cm
Package 1 Weight	7.5 kg
Unit Type Of Package 2	PAM
Number Of Units In Package 2	24
Package 2 Height	120 cm
Package 2 Width	100 cm
Package 2 Length	96 cm

Package 2 Weight

193 kg

## Sustainability

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

### Well-being performance



Mercury Free



Rohs Exemption Information

Yes

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations