

# Product data sheet

Specifications



2 Socket-outlet, New Unica,  
complete socket-outlet, 2P, 16A,  
European, with shutter, IP4X,  
glossy, untreated, beige

NU206344

## Main

|                            |                        |
|----------------------------|------------------------|
| Range                      | New Unica              |
| Product Or Component Type  | Socket-outlet          |
| Aesthetic Name             | Unica Studio           |
| Device Presentation        | Complete socket-outlet |
| Device Mounting            | Flush                  |
| Socket Number              | 2                      |
| Outlet Poles Configuration | 2P                     |
| Outlet Standard            | European               |
| Rated Current              | 16 A                   |

## Complementary

|                                |   |
|--------------------------------|---|
| Device Application             | Power supply  |
| Cover Type                     | With shutter  |
| [Ue] Rated Operational Voltage | 250 V   |
| Network Type                   | AC  |
| Network Frequency              | 50/60 Hz  |
| Fixing Mode                    | Screws  |
| Colour Tint                    | Beige (RAL 1013)  |
| Connections - Terminals        | Screw terminals   |
| Cable Cross Section            | 0...2.5 mm² cable(s), 2 - cable stiffness: flexible<br>0...2.5 mm² cable(s), 2 - cable stiffness: rigid |
| Minimum Load Breaking Capacity | 100 operations 1.25 In and 1.1 Un, cos phi = 0.6  |
| Electrical Durability          | 10000 cycles, cos phi = 0.8   |
| Insulation Resistance          | > 5 MOhm at 500 V   |
| Dielectric Strength            | 2000 V  |
| Material                       | PC: mechanism cover   |
| Surface Finish                 | Glossy  |
| Quantity Per Set               | Set of 1 flow-pack  |
| Standards                      | IEC 60884-1<br>UNE 20315-1-1<br>UNE 20315-1-2<br>NF C 61-314  |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|                               |   |
|-------------------------------|---|
| Product Certifications        | AENOR<br>NF<br>EAC  |
| Embedding Depth               | 24 mm   |
| Depth                         | 47 mm   |
| Width                         | 85 mm   |
| Height                        | 125 mm  |
| Net Weight                    | 0.099 kg  |
| Surface Treatment             | Untreated   |
| Resistance To Chemical Agents | Resistant to alcohol (70 %)<br>Resistant to alcohol (96 %)<br>Resistant to A-Lactic Acid<br>Resistant to diluted quaternary ammonium<br>Resistant to diluted bleach<br>Resistant to diluted ammonia<br>Resistant to soapy water<br>Resistant to crystal cleaner<br>Resistant to hydrogen peroxide 10 volumes<br>Resistant to hexane |

## Environment

|                                       |   |
|---------------------------------------|---|
| Ambient Air Temperature For Operation | -5...35 °C  |
| Ambient Air Temperature For Storage   | -5...50 °C  |
| Ik Degree Of Protection               | IK04  |
| Ip Degree Of Protection               | IP4X  |
| Environmental Characteristic          | Acetone<br>Bleach<br>UV resistant<br>Petrol<br>Oil<br>Alcohol<br>Window-cleaning fluid<br>Liquid soap |

## Packing Units

|                              |         |
|------------------------------|---------|
| Unit Type Of Package 1       | PCE     |
| Number Of Units In Package 1 | 1       |
| Package 1 Height             | 4.7 cm  |
| Package 1 Width              | 8.5 cm  |
| Package 1 Length             | 12.6 cm |
| Package 1 Weight             | 95 g    |
| Unit Type Of Package 2       | CAR     |
| Number Of Units In Package 2 | 5       |
| Package 2 Height             | 12 cm   |
| Package 2 Width              | 17.5 cm |
| Package 2 Length             | 26 cm   |
| Package 2 Weight             | 610 g   |
| Unit Type Of Package 3       | S04     |
| Number Of Units In Package 3 | 45      |
| Package 3 Height             | 30 cm   |

|                  |         |
|------------------|---------|
| Package 3 Width  | 40 cm   |
| Package 3 Length | 60 cm   |
| Package 3 Weight | 6.28 kg |

# Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



## Transparency

|                          |   |
|--------------------------|---|
| Eu Rohs Directive        | Under investigation   |
| Environmental Disclosure | <a href="#">Product Environmental Profile</a>   |
| Weee                     | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Circularity Profile      | No need of specific recycling operations  |