Specifications



## Primalum - emergency light block standard - non-maintained - 1 h -320 lm

OVA37078E

() Discontinued on: Dec 31, 2016

#### (!) Discontinued

#### Main

Range Of Product	Primalum
Product Or Component Type	Emergency light fitting
Function	Standard
Supply	Non-maintained
Light Source	Fluorescent tube 2G7 11 W
Number Of Batteries	1 x 6 V 2.2 Ah Ni-Cd (Nickel-Cadmium)
Wiring Device Additional Information	Personalized with coloured frames Can be inhibited with rest mode via Teleur range of remote controls

# Complementary

· · · · · · · · · · · · · · · · · · ·	
[Ue] Rated Operational Voltage	230 V 50 Hz
Power Consumption In Va	3.5 VA
Electrical Insulation Class	Class II
Autonomy	1 h
Charging Time	24 h
Luminous Flux	Emergency condition: 320 lm
Device Mounting	Surface ceiling Electrified track Flush false ceiling Flush wall Hanging ceiling Surface wall
Height	55 mm
Width	122 mm
Depth	270 mm
Net Weight	0.94 kg

### Environment

Ip Degree Of Protection	IP42
Ik Degree Of Protection	IK07
Ambient Air Temperature For Operation	040 °C
Fire Resistance	850 °C

# **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	6 cm
Package 1 Width	12.5 cm
Package 1 Length	31 cm
Package 1 Weight	940 g

## **Contractual warranty**

Warranty

18 months

### Sustainability

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



RoHS/REACh

#### **Certifications & Standards**

Eu Rohs Directive

Compliant EU RoHS Declaration