Product data sheet

Specifications





(!) Discontinued

Main

Astro Guida - emergency exit sign -
self-diagnosis - maintained - 1 h

OVA38466E

() Discontinued on: Feb 22, 2021

Range	Exiway
Product Name	Astro Guida
Product Or Component Type	Emergency exit sign
Function	Self-test
Supply	Maintained
Provided Equipment	5 pictogram stickers bracket flag installation

Complementary

Range Compatibility	TBS remote control
[Ue] Rated Operational Voltage	230 V 50 Hz
Power Consumption In Va	10 VA
Electrical Insulation Class	Class II
Battery Capacity	0.6 Ah at 4.8 V, Ni-Cd (Nickel-Cadmium)
Autonomy	1 h
Charging Time	12 h
Bulb Type	Cold cathode light 40000 h
Visibility Distance	24 m
Device Mounting	Surface ceiling Hanging ceiling Surface wall Electrified track Flag type bracket wall
Height	213 mm
Width	261 mm
Depth	35 mm
Net Weight	0.76 kg

Environment

Ip Degree Of Protection	IP42
Ik Degree Of Protection	IK06
Ambient Air Temperature For Operation	040 °C
Fire Resistance	850 °C

IEC 50-11 EN 60598-2-22 IEC 695-2-1 EN 1838 EN 60695-2-10

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	0.27 cm
Package 1 Width	27.8 cm
Package 1 Length	28.2 cm
Package 1 Weight	790 g

Contractual warranty

Warranty

18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



RoHS/REACh

Certifications & Standards

Eu Rohs Directive

Compliant EU RoHS Declaration