

Interlocked socket, Mureva PK, panel mounting, 63A, 3P+E, 400V, IP65

PKB63T534

Main

| Range | Mureva |
|---------------------------|--------------------|
| Product Or Component Type | Interlocked socket |
| Device Short Name | Mureva socket |
| Plug, Socket Category | Low voltage |
| Poles Description | 3P+E |
| Network Type | AC |
| Outlet Standard | Industrial |

Complementary

| Mounting Mode | Panel-mounted |
|--------------------------------|--------------------------------------------------|
| [In] Rated Current | 63 A |
| [Ue] Rated Operational Voltage | 380415 V |
| Network Frequency | 50/60 Hz |
| Ground Lug Clockwise Position | 6 h |
| Protection Type | Without protection |
| Plug, Socket Material | Housing: self-extinguishing polymer |
| Contacts Material | Pins: stainless steel Screws: stainless steel |
| Connections - Terminals | Captive screws |
| Maximum Cable Cross Section | 35 mm² |
| Maximum Cable Outer Diameter | 25 mm |
| Net Weight | 3 kg |
| Base Dimension | 140 x 430 mm |
| Height | 430 mm |
| Width | 140 mm |
| Depth | 116 mm |
| Colour | Grey (RAL 7035) |
| Voltage Colour | Red |

Environment

Standards IEC 60309-2 IEC 60309-1

| Ip Degree Of Protection | IP65 conforming to IEC 60529 |
|------------------------------------------|-------------------------------------|
| Ik Degree Of Protection | IK09 conforming to EN 62262 |
| Fire Resistance | 750 °C conforming to IEC 60695-2-11 |
| Relative Humidity | 50 % at 40 °C 70 % at 30 °C |
| Austriant Air Tanan austria Fan | 90 % at 20 °C |
| Ambient Air Temperature For Operation | 35 °C (86400 s) -2540 °C |

Packing Units

| Unit Type Of Package 1 | PCE |
|------------------------------|----------|
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 14.0 cm |
| Package 1 Width | 16.7 cm |
| Package 1 Length | 43.0 cm |
| Package 1 Weight | 2.6 kg |
| Unit Type Of Package 2 | P12 |
| Number Of Units In Package 2 | 9 |
| Package 2 Height | 80.0 cm |
| Package 2 Width | 80.0 cm |
| Package 2 Length | 120.0 cm |
| Package 2 Weight | 35.4 kg |

Contractual warranty

Warranty 18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >







Lower Impact Materials Transparency RoHS/REACh

Resource performance



Minimum Percentage Of Recycled Plastic Content

52

Well-being performance



Rohs Exemption Information

Yes

Certifications & Standards

| Reach Regulation | REACh Declaration |
|--------------------------|-----------------------------------------------------------------------------------------------------|
| Eu Rohs Directive | Pro-active compliance (Product out of EU RoHS legal scope) |
| China Rohs Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |