

# Product data sheet

Specifications



## RelayAux - flush mounting socket screw base for auxiliary relay connection

REL91356

### Main

Range Of Product	RelayAux
Product Or Component Type	Socket
Product Compatibility	REL9125x REL9124x
Device Mounting	Flush

### Complementary

Insulation Resistance Measurements	> 100 MOhm at 500 V DC conforming to IEC 60255-5
Contacts Material	AgNi
Mechanical Robustness	Shocks 11 ms (5 gn) conforming to IEC 60068-2-27 Bumps 16 ms (10 Gn) conforming to IEC 60068-2-29
Width	120 mm
Height	80 mm
Depth	101.5 mm
Net Weight	0.4 kg
[Uimp] Rated Impulse Withstand Voltage	5 kV during 1.2/50 $\mu$ s conforming to IEC 60255-5

### Environment

Maximum Relative Humidity	93 % at 40 °C
Electromagnetic Compatibility	Conducted and radiated emissions criteria A conforming to EN 55022 Conducted and radiated emissions criteria B conforming to EN 55022 Electrostatic discharge - test level: 15 kV level 4 (air discharge) conforming to IEC 61000-4-2 Electrostatic discharge - test level: 8 kV level 4 (contact discharge) conforming to IEC 61000-4-2 Radiated radio-frequency electromagnetic field immunity test - test level: 10 V/m, 80 MHz...1 GHz level 3 conforming to IEC 61000-4-3 Radiated radio-frequency electromagnetic field immunity test - test level: 10 V/m, 80 MHz...1 GHz level 3 conforming to ENV 50204 Electrical fast transient/burst immunity test - test level: 4 kV, 5 kHz level 4 (1 min) conforming to IEC 61000-4-4 Surge immunity test - test level: 2 kV level 3 (common mode) conforming to IEC 61000-4-5 Surge immunity test - test level: 1 kV level 3 (differential mode) conforming to IEC 61000-4-5 Conducted RF disturbances - test level: 10 V, 0.15...80 MHz level 3 conforming to IEC 61000-4-6 Magnetic field at power frequency - test level: 100 A/m level 5 (continuous) conforming to IEC 61000-4-8 Magnetic field at power frequency - test level: 1000 A/m level 5 (2 s) conforming to IEC 61000-4-8 Damped oscillating waves - test level: 2.5 kV, 1 MHz level 3 (common mode) conforming to IEC 60255-22-1 Damped oscillating waves - test level: 1 kV, 1 MHz level 3 (differential mode) conforming to IEC 60255-22-1

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Dielectric Strength	2 kV 50 Hz 1 min conforming to IEC 60255-5
Vibration Resistance	1 gn (f = 58...150 Hz) conforming to IEC 60068-2-1 +/- 0.075 mm (f = 10...58 Hz) conforming to IEC 60068-2-1
Ip Degree Of Protection	IP20 conforming to IEC 60529
Operating Altitude	< 2000 m
Fire Resistance	850 °C during 30 s
Directives	89/336/EEC - electromagnetic compatibility 93/68/EEC - low voltage directive 72/23/EEC - low voltage directive 92/31/EEC - electromagnetic compatibility
Product Certifications	CE UL listed file E322124
Ambient Air Temperature For Storage	-25...70 °C
Ambient Air Temperature For Operation	-25...70 °C

## Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	8.0 cm
Package 1 Width	12.0 cm
Package 1 Length	12.2 cm
Package 1 Weight	300.0 g