



Switch, Miluz, white moulded, 1-way, 10AX 250V, white -1 module

S3B72010

Main

Range	Miluz
Aesthetic Name	White moulded
Product Or Component Type	Switch

Complementary

Device Presentation	Mechanism
Type Of Packing	Flow-pack
Switch Function	1-way
Local Signalling	Without pilot light
Marking	1-L
[In] Rated Current	10 A
[Ue] Rated Operational Voltage	250 V AC
Material	ABS (acrylonitrile butadiene-styrene): wiring device
Number Of Modules	1 module
Fixing Mode	Clip-in
Connections - Terminals	Screw-clamp terminals
Cable Cross Section	4 mm²
Awg Gauge	AWG 12
Height	22 mm
Width	41.4 mm
Depth	36 mm
Embedding Depth	26 mm
Projecting Depth	10 mm

Environment

Standards	ABNT NBR NM 60.669
Product Certifications	RETIE NOM/ANCE

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1

Package 1 Height	4 cm
Package 1 Width	2.2 cm
Package 1 Length	4.4 cm
Package 1 Weight	16 g
Unit Type Of Package 2	CAR
Number Of Units In Package 2	50
Package 2 Height	15.8 cm
Package 2 Width	21.5 cm
Package 2 Length	26.5 cm
Package 2 Weight	1034 g

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

⊘	Reach Free Of Svhc		
⊘	Toxic Heavy Metal Free		
⊘	Mercury Free		
⊘	Rohs Exemption Information	Yes	

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations