

# Product data sheet

Specifications



## APC Smart-UPS VT 15kVA 208V w/ 2 Batt Mod Exp to 4, Start-Up 5X8, Int Maint Bypass, Parallel Capable

SUVP15KF2B4S

! Discontinued

! Discontinued on: Jul 5, 2021

! End-of-service on: Oct 18, 2023

### Overview

Lead Time Usually Ships within 2 Weeks

### Main

Main Input Voltage	208 V 3 phases
Other Input Voltage	220 V
Main Output Voltage	120 V 208 V 208 V 3 phases
Other Output Voltage	220 V
Rated Power In W	12000 W
Rated Power In Va	15000 VA
Output Connector Type	Hard wire 5-wire (3P + N + E) 1
Connections - Terminals	1 screw terminals
Provided Equipment	Battery modules ship installed CD with software Network management card Power modules ship installed Smart UPS signalling RS-232 cable User manual Bolt down brackets Installation guide Start up included

### Batteries & Runtime

Run Time	<a href="#">View Runtime Graph</a>
Efficiency	<a href="#">View Efficiency Graph</a>
Battery Type	VRLA
Number Of Battery Filled Slots	2
Number Of Battery Free Slots	2
Battery Recharge Time	5 h
Number Of Battery Replacement Quantity	2
Battery Voltage	+/- 192 V (split battery referenced to neutral)
Discharge Battery Voltage	+/- 154 V
Battery Charger Power	1015 W rated

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Battery Life	3...5 year(s)
Extended Runtime	1

## General

Ups Type	Double conversion online
Number Of Power Module Free Slots	0
Number Of Power Module Filled Slots	0
Redundant	Yes

## Physical

Colour	Black
Height	149.9 cm
Width	52.3 cm
Depth	81.3 cm
Net Weight	415 kg
Mounting Location	Front
Mounting Preference	No preference
Mounting Mode	Not rack-mountable
Two Post Mountable	0
Usb Compatible	No

## Input

Network Frequency	40...70 Hz
Number Of Input Connectors	1 hard wire 5-wire (3P + N + E)
Input Voltage Limits	165...240 V
Maximum Input Current	40 A
Switching Current Capacity	60 A
Input Power Factor At Full Load	0.98

## Output

Maximum Configurable Power In Va	15000 VA
Maximum Configurable Power In W	12000 W
Output Frequency	57...63 Hz for 60 Hz nominal sync to mains 60 Hz +/- 0.1 % for 60 Hz nominal unsynchronised
Wave Type	Sine wave
Harmonic Distortion	Less than 5 % at full load
Maximum Output Current	46 A
Crest Factor	Unlimited
Bypass Type	Built-in maintenance bypass Built-in static bypass
Additional Information	Configurable for 208 and 220V - 3 Phase

## Conformance

Product Certifications	cUL listed UL 1778
------------------------	-----------------------

## Environmental

Ambient Air Temperature For Operation	0...40 °C
Relative Humidity	0...95 %
Operating Altitude	0...3333 ft
Ambient Air Temperature For Storage	-50...40 °C
Storage Relative Humidity	0...95 %
Storage Altitude	0.00...15240.00 m
Acoustic Level	54 dBA
Heat Dissipation	3276 Btu/h
Nema Degree Of Protection	NEMA 1

## Communications & Management

Free Slots	0
Preinstalled Device	Network management card 2 with environmental monitoring
Emergency Power Off	Yes

## Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	164.3 cm
Package 1 Width	106.2 cm
Package 1 Length	65 cm
Package 1 Weight	445.91 kg

## Contractual warranty

Warranty	1 year repair or replace, Start-Up Service
----------	--




# Sustainability

**Green Premium™** label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Take-back   Transparency   RoHS/REACH

## Resource performance

✓

 Take-Back Program Available

## Well-being performance

✓

 Mercury Free

✓

 Rohs Exemption Information   [Yes](#)

## Certifications & Standards

Reach Regulation	<a href="#">REACH Declaration</a>
Eu Rohs Directive	Compliant with Exemptions
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>
California Proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="#">www.P65Warnings.ca.gov</a>