

Symmetra PX 160 Maintenance Bypass Panel, 400V

SYMBP160H

Overview

Presentation	Installed next to the UPS for convenient access, the 300mm Maintenance Bypass Panel isolates the UPS from the critical load during service procedures.
Lead Time	Usually Ships within 3 Weeks

Main

Main Input Voltage	400 V 3 phases	
Main Output Voltage	400 V 3 phases	
Connections - Terminals	1 screw terminal	

Physical

Colour	Black	
Height	200.4 cm	
Width	30 cm	
Depth	107 cm	
Net Weight	169 kg	
Mounting Location	Front	
Mounting Preference	No preference	
Mounting Mode	Not rack-mountable	

Input

Network Frequency	50 Hz
Number Of Input Connectors	1 hard wire 5-wire (3P + N + E)

Conformance

Standards	IEC 62040-1-1

Environmental

Ambient Air Temperature For Operation	040 °C
Relative Humidity	095 %
Operating Altitude	010000 ft
Ambient Air Temperature For Storage	-2565 °C
Storage Relative Humidity	095 %
Storage Altitude	0.0015240.00 m

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	215 cm
Package 1 Width	121 cm
Package 1 Length	84.8 cm
Package 1 Weight	189 kg

Contractual warranty

Warranty 1 year (parts only)

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Take-back

Resource performance



Take-Back Program Available

Well-being performance



Reach Free Of Svhc

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration