

Product data sheet

Specifications



Symmetra PX250/500 Third Party Switch Gear Kit

SYOPT007

Overview

Presentation	Ancillary Monitor Board, EPO Connection and Trip Board, and 50 meter connection cables for installing either the custom switchgear used in parallel Symmetra PX 250/500kW systems or a third-party maintenance bypass panel used with the Symmetra PX 250/500kW without MBwD UPS.
Lead Time	Usually Ships within 3 Weeks

Main

Provided Equipment	User manual
--------------------	-------------

Physical

Height	4.3 cm
Width	9.3 cm
Depth	3.5 cm
Net Weight	0.45 kg

Conformance

Product Certifications	CE UL recognized
------------------------	---------------------

Environmental

Ambient Air Temperature For Operation	0...40 °C
Operating Altitude	0...15000 ft
Relative Humidity	0...95 %
Ambient Air Temperature For Storage	0...40 °C
Storage Altitude	0.00...15240.00 m
Storage Relative Humidity	0...95 %

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	19.7 cm
Package 1 Width	8 cm
Package 1 Length	9.5 cm
Package 1 Weight	0.91 kg

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Contractual warranty

Warranty	1 year repair or replace
----------	--------------------------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

Eu Rohs Directive

Compliant

[EU RoHS Declaration](#)
