Specifications



() Discontinued

Ulti - 2 x 2.1A USB Charger Module - White

US32USB_WE

() Discontinued on: Feb 27, 2024

Main

Product Or Component Type	USB charger
Fixing Mode	Screw

Complementary

Device Mounting Flush Device Presentation Mechanism Colour Tint White Surface Finish Glossy Surface Treatment Untreated Number Of Modules 2 modules 46 x 36.7 x 21.7 mm Condition Of Use Room temperature Ambient Air Temperature For -560 °C Storage -560 °C Relative Humidity 1090 % [Ue] Rated Operational Voltage 100/240 V AC 50/60 Hz Integrated Connection Type 2 USB port 5 V DC, maximum load current: 2.1 A Material PA (polyamide) 6: housing Silicone rubber: cover PC (polycarbonate): grid plate Shape Of Screw Head Cross Number Of Terminals 2 screw terminals Clamping Connection Capacity 2.5 mm² for stranded cable(s) 1.5 mm² for rigid cable(s) With 87 mm Width 87 mm			
Colour Tint White Surface Finish Glossy Surface Treatment Untreated Number Of Modules 2 modules 46 x 36.7 x 21.7 mm Condition Of Use Room temperature Ambient Air Temperature For Storage -560 °C Relative Humidity 1090 % [Ue] Rated Operational Voltage 100/240 V AC 50/60 Hz Integrated Connection Type 2 USB port 5 V DC, maximum load current: 2.1 A Material PA (polyamide) 6: housing Silicone rubber: cover PC (polycarbonate): grid plate Shape Of Screw Head Cross Number Of Terminals 2 screw terminals Clamping Connection Capacity 2.5 mm² for stranded cable(s) 2.5 mm² for fistible cable(s) 1.5 mm² for rigid cable(s) 1.5 mm² for rigid cable(s) Vire Stripping Length 6 mm Product Compatibility HTC XiaoMii Apple Major smart phone and tablet Samsung HW 87 mm Product Compatibility HTC XiaoMii Apple	Device Mounting	Flush	
Surface Finish Glossy Surface Treatment Untreated Number Of Modules 2 modules 46 x 36.7 x 21.7 mm Condition Of Use Room temperature Ambient Air Temperature For Storage -560 °C Relative Humidity 1090 % [Ue] Rated Operational Voltage 100/240 V AC 50/60 Hz Integrated Connection Type 2 USB port 5 V DC, maximum load current: 2.1 A Material PA (polyamide) 6: housing Silicone rubber: cover PC (polycarbonate): grid plate Shape Of Screw Head Cross Number Of Terminals 2 screw terminals Clamping Connection Capacity 2.5 mm² for stranded cable(s) 2.5 mm² for flexible cable(s) 1.5 mm² for rigid cable(s) 1.5 mm² for flexible cable(s) 1.5 mm² for stranded cable(s) 1.5 mm² for flexible cable(s) 1.5 mm² for flexible cable(s) 1.5 mm² for stranded cable(s) 1.5 mm² for stranded cable(s) 1.5 mm² for flexible cable(s) 1.5 mm² for flexible cable(s) 1.5 mm² for stranded cable(s) 1.5 mm² for strand	Device Presentation	Mechanism	
Surface Treatment Untreated Number Of Modules 2 modules 46 x 36.7 x 21.7 mm Condition Of Use Room temperature Ambient Air Temperature For Storage -560 °C Relative Humidity 1090 % [Ue] Rated Operational Voltage 100/240 V AC 50/60 Hz Integrated Connection Type 2 USB port 5 V DC, maximum load current: 2.1 A Material PA (polyamide) 6: housing Silicone rubber: cover PC (polycarbonate): grid plate Shape Of Screw Head Cross Number Of Terminals 2 screw terminals Clamping Connection Capacity 2.5 mm² for stranded cable(s) 2.5 mm² for flexible cable(s) 2.5 mm² for flexible cable(s) 1.5 mm² for rigid cable(s) 1.5 mm² for rigid cable(s) 1.5 mm² for rigid cable(s) 1.5 mm² for flexible cable(s) 1.5 mm² for stranded cable(s) 1.5 mm² for rigid cable(s) 1.5 mm² for rigid cable(s) 1.5 mm² for stranded cable(s) 1.5 mm² for stranded cable(s) 1.5 mm² for stranded cable(s) 1.5 mm² for stranded cable(s) 1.5 mm² for stranded cable(s) 1.5 mm² for stranded cable(s) 1.5 mm² for stranded cable(s) 1.5 mm² for stranded cable(s) 1.5 mm² for stranded cable(s) 1.5 m² for stranded	Colour Tint	White	
Number Of Modules 2 modules 46 x 36.7 x 21.7 mm Condition Of Use Room temperature Ambient Air Temperature For Storage -560 °C Relative Humidity 1090 % [Ue] Rated Operational Voltage 100/240 V AC 50/60 Hz Integrated Connection Type 2 USB port 5 V DC, maximum load current: 2.1 A Material PA (polyamide) 6: housing Silicone rubber: cover PC (polycarbonate): grid plate Shape Of Screw Head Cross Number Of Terminals 2 screw terminals Olamping Connection Capacity 2.5 mm ² for stranded cable(s) 2.5 mm ² for rigid cable(s) .1.5 mm ² for rigid cable(s) 1.5 mm ² for rigid cable(s) .1.5 mm ² for rigid cable(s) 1.5 mm ² for rigid cable(s) .1.5 mm ² for rigid cable(s) 1.5 mm ² for rigid cable(s) .1.5 mm ² for rigid cable(s) 1.5 mm ² for rigid cable(s) .1.5 mm ² for rigid cable(s) 1.5 mm ² for rigid cable(s) .1.5 mm ² for rigid cable(s) 1.5 mm ² for rigid cable(s) .1.5 mm ² for rigid cable(s) 1.5 mm ² for rigid cable(s) .1.5 mm ² for rigid cable(s) 1.5 mm ² for rigid cable(s) .1.5 mm ² for rigid cable(s) 1.5 mm ² for rigid cable(s) .1.5 mm ² for rigid cable	Surface Finish	Glossy	
Condition Of Use Room temperature Ambient Air Temperature For Storage -560 °C Relative Humidity 1090 % [Ue] Rated Operational Voltage 100/240 V AC 50/60 Hz Integrated Connection Type 2 USB port 5 V DC, maximum load current: 2.1 A Material PA (polyamide) 6: housing Silicone rubber: cover PC (polycarbonate): grid plate Shape Of Screw Head Cross Number Of Terminals 2 screw terminals Clamping Connection Capacity 2.5 mm² for stranded cable(s) 2.5 mm² for rigid cable(s) 1.5 mm² for rigid cable(s) Vire Stripping Length 6 mm Product Compatibility HTC XiaoMi Apple HW Product Compatibility HTC XiaoMi Apple HW Height 87 mm	Surface Treatment	Untreated	
Ambient Air Temperature For Storage -560 °C Relative Humidity 1090 % [Ue] Rated Operational Voltage 100/240 V AC 50/60 Hz Integrated Connection Type 2 USB port 5 V DC, maximum load current: 2.1 A Material PA (polyamide) 6: housing Silicone rubber: cover PC (polycarbonate): grid plate Shape Of Screw Head Cross Number Of Terminals 2 screw terminals Clamping Connection Capacity 2.5 mm² for stranded cable(s) 2.5 mm² for flexible cable(s) 1.5 mm² for stranded cable(s) 1.5 mm² for fiexible cable(s) 1.5 mm² for fiexible cable(s) 1.5 mm² for grid cable(s) 1.5 mm² for stranded cable(s) 1.5 mm² for grid cable(s) 1.5 mm² for grid cable(s) 1.5 mm² for stranded cable(s) 1.5 mm² for grid cable(s) 1.5 mm² for migid cable(s) 1.5 mm² for migid cable(s) 1.5 mm² for stranded cable(s) Wire Stripping Length 6 mm Product Compatibility HTC XiaoMii Apple Major smart phone and tablet Samsung HW Power bank Height 87 mm	Number Of Modules	2 modules 46 x 36.7 x 21.7 mm	
Storage Relative Humidity 1090 % [Ue] Rated Operational Voltage 100/240 V AC 50/60 Hz Integrated Connection Type 2 USB port 5 V DC, maximum load current: 2.1 A Material PA (polyamide) 6: housing Silicone rubber: cover PC (polycarbonate): grid plate Shape Of Screw Head Cross Number Of Terminals 2 screw terminals Clamping Connection Capacity 2.5 mm² for stranded cable(s) 2.5 mm² for rigid cable(s) 1.5 mm² for flexible cable(s) 1.5 mm² for rigid cable(s) 1.5 mm² for rigid cable(s) 1.5 mm² for rigid cable(s) 1.5 mm² for rigid cable(s) Wire Stripping Length 6 mm Product Compatibility HTC XiaoMi Apple Major smart phone and tablet Samsung HW Power bank Height 87 mm	Condition Of Use	Room temperature	
[Ue] Rated Operational Voltage 100/240 V AC 50/60 Hz Integrated Connection Type 2 USB port 5 V DC, maximum load current: 2.1 A Material PA (polyamide) 6: housing Silicone rubber: cover PC (polycarbonate): grid plate Shape Of Screw Head Cross Number Of Terminals 2 screw terminals Clamping Connection Capacity 2.5 mm² for stranded cable(s) 2.5 mm² for flexible cable(s) 1.5 mm² for rigid cable(s) 1.5 mm² for rigid cable(s) 1.5 mm² for rigid cable(s) 1.5 mm² for rigid cable(s) Wire Stripping Length 6 mm Product Compatibility HTC XiaoMi Apple Major smart phone and tablet Samsung HW Height 87 mm		-560 °C	
Integrated Connection Type 2 USB port 5 V DC, maximum load current: 2.1 A Material PA (polyamide) 6: housing Silicone rubber: cover PC (polycarbonate): grid plate Shape Of Screw Head Cross Number Of Terminals 2 screw terminals Clamping Connection Capacity 2.5 mm² for stranded cable(s) 2.5 mm² for rigid cable(s) 1.5 mm² for rigid cable(s) 1.5 mm² for rigid cable(s) 1.5 mm² for rigid cable(s) 1.5 mm² for rigid cable(s) Wire Stripping Length 6 mm Product Compatibility HTC XiaoMi Apple Major smart phone and tablet Samsung HW Height 87 mm	Relative Humidity	1090 %	
Material PA (polyamide) 6: housing Silicone rubber: cover PC (polycarbonate): grid plate Shape Of Screw Head Cross Number Of Terminals 2 screw terminals Clamping Connection Capacity 2.5 mm² for stranded cable(s) 2.5 mm² for flexible cable(s) 2.5 mm² for rigid cable(s) 1.5 mm² for rigid cable(s) 1.5 mm² for rigid cable(s) 1.5 mm² for rigid cable(s) Wire Stripping Length 6 mm Product Compatibility HTC XiaoMi Apple Major smart phone and tablet Samsung HW Power bank Height 87 mm	[Ue] Rated Operational Voltage	100/240 V AC 50/60 Hz	
Silicone rubber: cover PC (polycarbonate): grid plate Shape Of Screw Head Cross Number Of Terminals 2 screw terminals Clamping Connection Capacity 2.5 mm² for stranded cable(s) 2.5 mm² for figuid cable(s) 1.5 mm² for stranded cable(s) 1.5 mm² for stranded cable(s) 1.5 mm² for stranded cable(s) 1.5 mm² for figuid cable(s) Wire Stripping Length 6 mm Product Compatibility HTC XiaoMi Apple Major smart phone and tablet Samsung HW Power bank Height 87 mm	Integrated Connection Type	2 USB port 5 V DC, maximum load current: 2.1 A	
Number Of Terminals 2 screw terminals Clamping Connection Capacity 2.5 mm² for stranded cable(s) 2.5 mm² for flexible cable(s) 2.5 mm² for rigid cable(s) 2.5 mm² for rigid cable(s) 1.5 mm² for stranded cable(s) 1.5 mm² for rigid cable(s) 1.5 mm² for rigid cable(s) 1.5 mm² for rigid cable(s) 1.5 mm² for rigid cable(s) 1.5 mm² for rigid cable(s) 1.5 mm² for rigid cable(s) 1.5 mm² for rigid cable(s) 1.5 mm² for rigid cable(s) Wire Stripping Length 6 mm Product Compatibility HTC XiaoMi Apple Major smart phone and tablet Samsung HW Power bank 87 mm	Material	Silicone rubber: cover	
Clamping Connection Capacity 2.5 mm² for stranded cable(s) 2.5 mm² for flexible cable(s) 2.5 mm² for rigid cable(s) 2.5 mm² for stranded cable(s) 1.5 mm² for stranded cable(s) 1.5 mm² for flexible cable(s) 1.5 mm² for rigid cable(s) 1.5 mm² for rigid cable(s) 1.5 mm² for rigid cable(s) 1.5 mm² for rigid cable(s) 1.5 mm² for rigid cable(s) Vire Stripping Length 6 mm Product Compatibility HTC XiaoMi Apple Major smart phone and tablet Samsung HW Power bank Height 87 mm	Shape Of Screw Head	Cross	
2.5 mm² for flexible cable(s) 2.5 mm² for rigid cable(s) 1.5 mm² for stranded cable(s) 1.5 mm² for rigid cable(s) Vire Stripping Length 6 mm Product Compatibility HTC XiaoMi Apple Major smart phone and tablet Samsung HW Power bank	Number Of Terminals	2 screw terminals	
Product Compatibility HTC XiaoMi Apple Major smart phone and tablet Samsung HW Power bank Height 87 mm	Clamping Connection Capacity	 2.5 mm² for flexible cable(s) 2.5 mm² for rigid cable(s) 1.5 mm² for stranded cable(s) 1.5 mm² for flexible cable(s) 	
XiaoMi Apple Major smart phone and tablet Samsung HW Power bank	Wire Stripping Length	6 mm	
	Product Compatibility	XiaoMi Apple Major smart phone and tablet Samsung HW	
Width 87 mm	Height	87 mm	
	Width	87 mm	

Depth	39 mm
Embedding Depth	29.3 mm
Net Weight	0.1136 kg

Environment

Product Certifications	IEC CCC
Ip Degree Of Protection	IP20
Environmental Characteristic	Liquid soap Alcohol

Packing Units

-	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	4.5 cm
Package 1 Width	11.2 cm
Package 1 Length	11.2 cm
Package 1 Weight	245 g
Unit Type Of Package 2	CAR
Number Of Units In Package 2	30
Package 2 Height	18 cm
Package 2 Width	31.2 cm
Package 2 Length	56.3 cm
Package 2 Weight	7650 g

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >




Eq

Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc



Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations