Specifications



automatic PowerLogic PFC Capacitor base, 500kvar 400-415V/ 50Hz tuning factor 3.8

VLVB208

Main

| Network Rated Voltage | 400 V AC 50 Hz 415 V AC 50 Hz |
|-----------------------|---|
| Reactive Power Rating | 500 kvar |
| Operating Mode | Automatic |
| Range Of Product | PowerLogic |
| Device Short Name | automatic capacitor bank with detuned reactor |

Complementary

| Complementary | |
|---|---|
| Network Pollution Level | Polluted |
| [Gh/Sn] Harmonic Pollution Rate | 2550 % |
| [Thdu] Total Harmonic Distorsion | 58 % |
| Tuning Factor | 3.8 |
| Tuning Frequency | 190 Hz |
| Step Sequences | 1.1.2 |
| Power Per Step | 50 kvar |
| Step Composition | 2x50 + 4x100 |
| Capacitor Technology | HDuty + detuned reactors |
| Step Protection Type | Overload: step circuit breaker Short-circuit: step circuit breaker |
| Poles Description | 3P |
| Capacitance Tolerance | - 5 % to 10 % |
| [Ui] Rated Insulation Voltage | 800 V |
| [Uimp] Rated Impulse Withstand Voltage | 8 kV |
| Maximum Permissible Voltage | 1.1 x Un (8 hours over 24 hours) conforming to IEC 60831 |
| [Imp] Maximum Permanent Current | 1.19 x In at 400 V conforming to IEC 60831 |
| Colour | White (RAL 9003) |
| Maximum Weight | 952 kg |
| Height | 2200 mm |
| Width | 800 mm capacitor: 600 mm detuned reactor: |
| Depth | 600 mm |

Environment

| Standards | IEC 61921 IEC 61439-1 IEC 61439-2 |
|--|---|
| Mounting Location | Indoor |
| Ik Degree Of Protection | IK10 |
| Relative Humidity | 095 % |
| Operating Altitude | <= 2000 m |
| Ambient Air Temperature For Operation | -540 °C |
| Average Ambient Air Temperature | 35 °C (over 24 hours) |

Average Ambient Air Temperature 35 °C (over 24 hours) For Operation

Packing Units

| - | |
|------------------------------|----------|
| Unit Type Of Package 1 | PCE |
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 1.0 cm |
| Package 1 Width | 2.0 cm |
| Package 1 Length | 3.0 cm |
| Package 1 Weight | 952.0 kg |

Contractual warranty

Warranty

18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Eu Rohs Directive

Not applicable, out of EU RoHS legal scope