

# automatic PowerLogic PFC Capacitor base, 600kvar 400-415V/ 50Hz tuning factor 2.7

VLVB210

#### Main

Network Rated Voltage	400 V AC 50 Hz 415 V AC 50 Hz
Reactive Power Rating	600 kvar
Operating Mode	Automatic
Range Of Product	PowerLogic
Device Short Name	automatic canacitor bank with detuned reactor

### Complementary

Network Pollution Level	Polluted
[Gh/Sn] Harmonic Pollution Rate	2550 %
[Thdu] Total Harmonic Distorsion	58 %
Tuning Factor	2.7
Tuning Frequency	135 Hz
Step Sequences	1.1.1
Power Per Step	100 kvar
Step Composition	6x100
Capacitor Technology	HDuty + detuned reactors
Step Protection Type	Overload: step circuit breaker Short-circuit: step circuit breaker
Poles Description	3P
Capacitance Tolerance	- 5 % to 10 %
[Ui] Rated Insulation Voltage	800 V
[Uimp] Rated Impulse Withstand Voltage	8 kV
Maximum Permissible Voltage	1.1 x Un (8 hours over 24 hours) conforming to IEC 60831
[Imp] Maximum Permanent Current	1.12 x In at 400 V conforming to IEC 60831
Colour	White (RAL 9003)
Location Of Connection	Bottom
Maximum Weight	952 kg
Height	2200 mm
Width	800 mm capacitor: 600 mm detuned reactor:
Depth	600 mm

#### **Environment**

Standards	IEC 61439-2 IEC 61439-1 IEC 61921
Mounting Location	Indoor
Ik Degree Of Protection	IK10
Relative Humidity	095 %
Operating Altitude	<= 2000 m
Ambient Air Temperature For Operation	-540 °C
Average Ambient Air Temperature For Operation	35 °C (over 24 hours)

# **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	1.0 cm
Package 1 Width	2.0 cm
Package 1 Length	3.0 cm
Package 1 Weight	952.0 kg

# **Contractual warranty**

Warranty 18 months

#### Sustainability

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

**Eu Rohs Directive** 

Not applicable, out of EU RoHS legal scope