

Product data sheet

Specifications



active infeed converter - 275 kW - 380...480 V

VW3A7254

⚠ To be discontinued on: Dec 31, 2024

⚠ To be end-of-service on: Dec 31, 2032

⚠ To be discontinued

Main

Device Short Name	AIC
Network Number Of Phases	3 phases
[Us] Rated Supply Voltage	380...480 V +/- 10 %
Network Frequency	50/60 Hz
Rated Power In W	275 kW
Range Compatibility	Altivar 61 Altivar 71
Product Specific Application	Component of the Active Front End Low harmonics Energy regeneration
Product Compatibility	ATV61HC25N4D 380...440 V AC with one variable speed drive ATV71HC20N4D 380...440 V AC with one variable speed drive ATV61HC25N4D 480 V AC with one variable speed drive ATV71HC20N4D 480 V AC with one variable speed drive ATV61H075N4...C63N4D DC with several variable speed drive on a common DC bus ATV71H075N4...C50N4D DC with several variable speed drive on a common DC bus
Assembly Style	Built-in unit
Type Of Cooling	Forced convection

Complementary

Line Current	395 A at 400 V 395 A at 480 V
Input Power	273 kW at 400 V 320 kW at 480 V
Continuous Output Current	412 A at 400 V 412 A at 480 V
Output Voltage	650 V DC - supply: 380...400 V AC 720 V DC - supply: 440 V AC 770 V DC - supply: 480 V AC
Thermal Losses	4710 W
Max Current	1.20 x nominal current (duration = 60 s) 1.35 x nominal current (duration = 2 s)
Maximum Voltage Drop At Rated Load	<30 % at 380...400 V, <= 60 s <40 % at 440 V, <= 60 s <40 % at 480 V, <= 60 s
Communication Port Protocol	Modbus CANopen

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Connector Type	1 RJ45 for Modbus Male SUB-D 9 on RJ45 for CANopen
Option Card	Communication bridge
Operating Position	Vertical +/- 10 degree
Height	950 mm
Width	585 mm
Depth	377 mm
Net Weight	140 kg

Environment

Environmental Characteristic	3K3 conforming to EN/IEC 60721-3-3 3C2 conforming to EN 60721-3-3 3S2 conforming to EN 60721-3-3
Relative Humidity	0...95 %
Ambient Air Temperature For Operation	45...60 °C (with current derating of 2 % per °C) -10...45 °C
Ambient Air Temperature For Storage	-25...70 °C
Operating Altitude	<= 1000 m without derating 1000...3000 m with current derating 1 % per 100 m
Pollution Degree	2 conforming to EN 61800-5-1
Vibration Resistance	1.5 mm (f= 3...10 Hz) conforming to EN/IEC 60068-2-6 0.6 gn (f= 10...200 Hz) conforming to EN/IEC 60068-2-6
Shock Resistance	4 gn for 11 ms conforming to EN/IEC 60721-3-3
Air Flow Surface	1000 cm²
Volume Of Cooling Air	1200 m3/h for power circuit 270 m3/h for control circuit
Ip Degree Of Protection	IP00
Standards	EN/IEC 61800-5-1
Product Certifications	UL (pending) CE CSA (pending)

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	53.0 cm
Package 1 Width	64.0 cm
Package 1 Length	129.0 cm
Package 1 Weight	160.0 kg

Contractual warranty

Warranty	18 months
----------	-----------

Sustainability



Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

Well-being performance

 Mercury Free	
 Rohs Exemption Information	Yes
Reach Regulation	REACH Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins