Specifications



Wear part, enclosure door, fan for variable speed drive, Altivar Process 600 900, from 110 to 315kW, from 380 to 440V

VX5VPM002

Main

Altivar Process 600/900
Enclosure door fan
Cooling accessory
Fan
0.8 kg

Complementary

Kit Composition	Fan Mounting bracket Instruction sheet
Product Compatibility	Variable speed drive ATV630 floor-standing 110 kW 380440 V Variable speed drive ATV630 floor-standing 132 kW 380440 V Variable speed drive ATV630 floor-standing 160 kW 380440 V Variable speed drive ATV630 floor-standing 200 kW 380440 V Variable speed drive ATV630 floor-standing 250 kW 380440 V Variable speed drive ATV630 floor-standing 315 kW 380440 V Variable speed drive ATV650 floor-standing 110 kW 380440 V Variable speed drive ATV650 floor-standing 132 kW 380440 V Variable speed drive ATV650 floor-standing 132 kW 380440 V Variable speed drive ATV650 floor-standing 106 kW 380440 V Variable speed drive ATV650 floor-standing 200 kW 380440 V Variable speed drive ATV650 floor-standing 200 kW 380440 V Variable speed drive ATV650 floor-standing 200 kW 380440 V Variable speed drive ATV650 floor-standing 110 kW 380440 V Variable speed drive ATV650 floor-standing 110 kW 380440 V Variable speed drive ATV650 floor-standing 110 kW 380440 V Variable speed drive ATV930 floor-standing 12 kW 380440 V Variable speed drive ATV930 floor-standing 120 kW 380440 V Variable speed drive ATV930 floor-standing 120 kW 380440 V Variable speed drive ATV930 floor-standing 100 kW 380440 V Variable speed drive ATV930 floor-standing 100 kW 380440 V Variable speed drive ATV950 floor-standing 110 kW 380440 V Variable speed drive ATV950 floor-standing 110 kW 380440 V Variable speed drive ATV950 floor-standing 135 kW 380440 V Variable speed drive ATV950 floor-standing 136 kW 380440 V Variable speed drive ATV950 floor-standing 100 kW 380440 V Variable speed drive ATV950 floor-standing 200 kW 380440 V Variable speed drive ATV950 floor-standing 200 kW 380440 V Variable speed drive ATV950 floor-standing 200 kW 380440 V

Packing Units

•	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	9.5 cm
Package 1 Width	30.0 cm
Package 1 Length	30.5 cm
Package 1 Weight	0.8 kg
Unit Type Of Package 2	S04
Number Of Units In Package 2	3

Package 2 Height	30.0 cm	
Package 2 Width	40.0 cm	
Package 2 Length	60.0 cm	
Package 2 Weight	2.247	
Fackage z weight	3.317 kg	

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Well-being performance

Reach Free Of Svhc	
Mercury Free	
Rohs Exemption Information	Yes
Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information