
Product datasheet

Specifications





() Discontinued

MOUNTING PLATE NSX/CVS/ VIGI/INS 630 V. FIX. TOGGLE

03080

() Discontinued on: 15 Jun 2023

Price: 1,340.12 ZAR

Main

Range	Prisma
Range Of Product	Prisma G
Product Or Component Type	Mounting plate
Accessory / Separate Part Category	Installation accessory
Range Compatibility	Prisma Prisma G duct
Installation Description	Floor-standing duct - width 300 mm Wall-mounted duct - width 300 mm
Installed Device	EasyPact: fixed CVS400 without earth leakage protection - control: toggle - vertical installation EasyPact: fixed CVS630 without earth leakage protection - control: toggle - vertical installation ComPact: fixed INS320400 - control: direct front rotary handle - vertical installation ComPact: fixed INS500630 - control: direct front rotary handle - vertical installation ComPact: fixed INV320400 - control: direct front rotary handle - vertical installation ComPact: fixed INV300630 - control: direct front rotary handle - vertical installation ComPact: fixed INV500630 - control: direct front rotary handle - vertical installation ComPact: fixed INV500630 - control: direct front rotary handle - vertical installation ComPact: fixed NSX400 without earth leakage protection - control: toggle - vertical installation ComPact: fixed NSX630 without earth leakage protection - control: toggle - vertical installation EasyPact: fixed CVS630 with earth leakage protection - control: toggle - vertical installation EasyPact: fixed NSX400 with earth leakage protection - control: toggle - vertical installation ComPact: fixed NSX400 with earth leakage protection - control: toggle - vertical installation ComPact: fixed NSX400 with earth leakage protection - control: toggle - vertical installation
Poles Description	1 x 3P: fixed CVS400 vertical installation 1 x 4P: fixed CVS400 vertical installation 1 x 3P: fixed CVS630 vertical installation 1 x 4P: fixed CVS630 vertical installation 1 x 4P: fixed INS320400 vertical installation 1 x 4P: fixed INS520400 vertical installation 1 x 4P: fixed INS500630 vertical installation 1 x 4P: fixed INS500630 vertical installation 1 x 4P: fixed INV320400 vertical installation 1 x 4P: fixed INV500630 vertical installation 1 x 4P: fixed INV500630 vertical installation 1 x 4P: fixed INV500630 vertical installation 1 x 4P: fixed INS400 vertical installation 1 x 4P: fixed NSX400 vertical installation 1 x 4P: fixed NSX630 vertical installation 1 x 4P: fixed NSX630 vertical installation 1 x 4P: fixed NSX630 vertical installation

Need additional plate (1M high) when installation of device is in vertical

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Life Is On Schneider

Product Certifications	ASEEA
Standards	IEC 61439-2
	14 module(s): NSX630 with earth leakage protection , direct with long terminal shield in 300 mm Widewall-mounted duct (cable coming from top or bottom of enclosure)
	in 300 mm Widefloor-standing duct (cable coming from top or bottom of enclosure)
	in 300 mm Widewall-mounted duct (cable coming from top or bottom of enclosure) 14 module(s): NSX630 with earth leakage protection , direct with long terminal shield
	14 module(s): NSX400 with earth leakage protection , direct with long terminal shield in 200 mm Widewall mounted duct (cable coming from top or bottom of applesure)
	in 300 mm Widefloor-standing duct (cable coming from top or bottom of enclosure)
	14 module(s): NSX400 with earth leakage protection , direct with long terminal shield
	in 300 mm Widewall-mounted duct (cable coming from top or bottom of enclosure)
	in 300 mm Widefloor-standing duct (cable coming from top or bottom of enclosure) 13 module(s): CVS630 with earth leakage protection , direct with long terminal shield
	13 module(s): CVS630 with earth leakage protection , direct with long terminal shield in 200 mm Widefleer atoming duct (cable coming from top or bottom of appleauro)
	in 300 mm Widewall-mounted duct (cable coming from top or bottom of enclosure)
	13 module(s): CVS400 with earth leakage protection , direct with long terminal shield
	in 300 mm Widefloor-standing duct (cable coming from top or bottom of enclosure)
	13 module(s): CVS400 with earth leakage protection , direct with long terminal shield
	shield in 300 mm Widewall-mounted duct (cable coming from top or bottom of enclosure)
	12 module(s): NSX630 without earth leakage protection , direct with long terminal
	enclosure)
	shield in 300 mm Widefloor-standing duct (cable coming from top or bottom of
	12 module(s): NSX630 without earth leakage protection , direct with long terminal
	shield in 300 mm Widewall-mounted duct (cable coming from top or bottom of enclosure)
	12 module(s): NSX400 without earth leakage protection , direct with long terminal
	enclosure)
	shield in 300 mm Widefloor-standing duct (cable coming from top or bottom of
	12 module(s): NSX400 without earth leakage protection , direct with long terminal
	mounted duct (cable coming from top or bottom of enclosure)
	standing duct (cable coming from top or bottom of enclosure) 12 module(s): INV500630, direct with long terminal shield in 300 mm Widewall-
	12 module(s): INV500630, direct with long terminal shield in 300 mm Widefloor-
	mounted duct (cable coming from top or bottom of enclosure)
	10 module(s): INV320400, direct with long terminal shield in 300 mm Widewall-
	standing duct (cable coming from top or bottom of enclosure)
	mounted duct (cable coming from top or bottom of enclosure) 10 module(s): INV320400, direct with long terminal shield in 300 mm Widefloor-
	12 module(s): INS500630, direct with long terminal shield in 300 mm Widewall-
	standing duct (cable coming from top or bottom of enclosure)
Mm]	12 module(s): INS500630, direct with long terminal shield in 300 mm Widefloor-
	mounted duct (cable coming from top or bottom of enclosure)
	standing duct (cable coming from top or bottom of enclosure) 10 module(s): INS320400, direct with long terminal shield in 300 mm Widewall-
	10 module(s): INS320400, direct with long terminal shield in 300 mm Widefloor-
	enclosure)
	shield in 300 mm Widewall-mounted duct (cable coming from top or bottom of
	12 module(s): CVS630 without earth leakage protection , direct with long terminal
	shield in 300 mm Widefloor-standing duct (cable coming from top or bottom of enclosure)
	12 module(s): CVS630 without earth leakage protection , direct with long terminal shield in 300 mm Widefloor-standing duct (cable coming from top or bottom of
	shield in 300 mm Widewall-mounted duct (cable coming from top or bottom of
	12 module(s): CVS400 without earth leakage protection , direct with long terminal
	enclosure)
	shield in 300 mm Widefloor-standing duct (cable coming from top or bottom of

Product Certifications

ASEFA

Complementary

Protective Treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
Surface Finish	Matt Smooth
Colour	White (RAL 9001)
Width	300 mm
Height	350 mm
Net Weight	0.78 kg

_

Functional Unit

300 mm Prisma G floor-standing duct EasyPact CVS400 without fixed toggle vertical 3P 1 direct with long terminal shield 12 216 mm 300 mm Prisma G wall-mounted duct EasyPact CVS400 without fixed toggle vertical 3P 1 direct with long terminal shield 12 216 mm 300 mm Prisma G floor-standing duct EasyPact CVS400 without fixed toggle vertical 4P 1 direct with long terminal shield 12 216 mm 300 mm Prisma G wall-mounted duct EasyPact CVS400 without fixed toggle vertical 4P 1 direct with long terminal shield 12 216 mm 300 mm Prisma G floor-standing duct EasyPact CVS630 without fixed toggle vertical 3P 1 direct with long terminal shield 12 216 mm 300 mm Prisma G wall-mounted duct EasyPact CVS630 without fixed toggle vertical 3P 1 direct with long terminal shield 12 216 mm 300 mm Prisma G floor-standing duct EasyPact CVS630 without fixed toggle vertical 4P 1 direct with long terminal shield 12 216 mm 300 mm Prisma G wall-mounted duct EasyPact CVS630 without fixed toggle vertical 4P 1 direct with long terminal shield 12 216 mm 300 mm Prisma G floor-standing duct ComPact INS320...400 fixed direct front rotary handle vertical 3P 1 direct with long terminal shield 10 166 mm 300 mm Prisma G wall-mounted duct ComPact INS320...400 fixed direct front rotary handle vertical 3P 1 direct with long terminal shield 10 166 mm 300 mm Prisma G floor-standing duct ComPact INS320...400 fixed direct front rotary handle vertical 4P 1 direct with long terminal shield 10 166 mm 300 mm Prisma G wall-mounted duct ComPact INS320...400 fixed direct front rotary handle vertical 4P 1 direct with long terminal shield 10 166 mm 300 mm Prisma G floor-standing duct ComPact INS500...630 fixed direct front rotary handle vertical 3P 1 direct with long terminal shield 12 266 mm 300 mm Prisma G wall-mounted duct ComPact INS500...630 fixed direct front rotary handle vertical 3P 1 direct with long terminal shield 12 266 mm 300 mm Prisma G floor-standing duct ComPact INS500...630 fixed direct front rotary handle vertical 4P 1 direct with long terminal shield 12 266 mm 300 mm Prisma G wall-mounted duct ComPact INS500...630 fixed direct front rotary handle vertical 4P 1 direct with long terminal shield 12 266 mm 300 mm Prisma G floor-standing duct ComPact INV320...400 fixed direct front rotary handle vertical 3P 1 direct with long terminal shield 10 166 mm 300 mm Prisma G wall-mounted duct ComPact INV320...400 fixed direct front rotary handle vertical 3P 1 direct with long terminal shield 10 166 mm 300 mm Prisma G floor-standing duct ComPact INV320...400 fixed direct front rotary handle vertical 4P 1 direct with long terminal shield 10 166 mm 300 mm Prisma G wall-mounted duct ComPact INV320...400 fixed direct front rotary handle vertical 4P 1 direct with long terminal shield 10 166 mm 300 mm Prisma G floor-standing duct ComPact INV500...630 fixed direct front rotary handle vertical 3P 1 direct with long terminal shield 12 266 mm 300 mm Prisma G wall-mounted duct ComPact INV500...630 fixed direct front rotary handle vertical 3P 1 direct with long terminal shield 12 266 mm 300 mm Prisma G floor-standing duct ComPact INV500...630 fixed direct front rotary handle vertical 4P 1 direct with long terminal shield 12 266 mm 300 mm Prisma G wall-mounted duct ComPact INV500...630 fixed direct front rotary handle vertical 4P 1 direct with long terminal shield 12 266 mm 300 mm Prisma G floor-standing duct ComPact NSX400 without fixed toggle vertical 3P 1 direct with long terminal shield 12 216 mm 300 mm Prisma G wall-mounted duct ComPact NSX400 without fixed toggle vertical 3P 1 direct with long terminal shield 12 216 mm 300 mm Prisma G floor-standing duct ComPact NSX400 without fixed toggle vertical 4P 1 direct with long terminal shield 12 216 mm 300 mm Prisma G wall-mounted duct ComPact NSX400 without fixed toggle vertical 4P 1 direct with long terminal shield 12 216 mm 300 mm Prisma G floor-standing duct ComPact NSX630 without fixed toggle vertical 3P 1 direct with long terminal shield 12 216 mm 300 mm Prisma G wall-mounted duct ComPact NSX630 without fixed toggle vertical 3P 1 direct with long terminal shield 12 216 mm 300 mm Prisma G floor-standing duct ComPact NSX630 without fixed toggle vertical 4P 1 direct with long terminal shield 12 216 mm 300 mm Prisma G wall-mounted duct ComPact NSX630 without fixed toggle vertical 4P 1 direct with long terminal shield 12 216 mm 300 mm Prisma G floor-standing duct EasyPact CVS400 with fixed toggle vertical 3P 1 direct with long terminal shield 13 366 mm 300 mm Prisma G wall-mounted duct EasyPact CVS400 with fixed toggle vertical 3P 1 direct with long terminal shield 13 366 mm 300 mm Prisma G floor-standing duct EasyPact CVS400 with fixed toggle vertical 4P 1 direct with long terminal shield 13 366 mm 300 mm Prisma G wall-mounted duct EasyPact CVS400 with fixed toggle vertical 4P 1 direct with long terminal shield 13 366 mm 300 mm Prisma G floor-standing duct EasyPact CVS630 with fixed toggle vertical 3P 1 direct with long terminal shield 13 366 mm 300 mm Prisma G wall-mounted duct EasyPact CVS630 with fixed toggle vertical 3P 1 direct with long terminal shield 13 366 mm 300 mm Prisma G floor-standing duct EasyPact CVS630 with fixed toggle vertical 4P 1 direct with long terminal shield 13 366 mm

300 mm Prisma G wall-mounted duct EasyPact CVS630 with fixed toggle vertical 4P 1 direct with long terminal shield 13 366 mm

300 mm Prisma G wall-mounted duct ComPact NSX400 with fixed toggle vertical 3P 1 direct with long terminal shield 14 266 mm

300 mm Prisma G floor-standing duct ComPact NSX400 with fixed toggle vertical 4P 1 direct with long terminal shield 14 266 mm

300 mm Prisma G wall-mounted duct ComPact NSX400 with fixed toggle vertical 4P 1 direct with long terminal shield 14 266 mm

300 mm Prisma G floor-standing duct ComPact NSX630 with fixed toggle vertical 3P

1 direct with long terminal shield 14 266 mm

300 mm Prisma G wall-mounted duct ComPact NSX630 with fixed toggle vertical 3P 1 direct with long terminal shield 14 266 mm

300 mm Prisma G floor-standing duct ComPact NSX630 with fixed toggle vertical 4P 1 direct with long terminal shield 14 266 mm

300 mm Prisma G wall-mounted duct ComPact NSX630 with fixed toggle vertical 4P

1 direct with long terminal shield 14 266 mm

³⁰⁰ mm Prisma G floor-standing duct ComPact NSX400 with fixed toggle vertical 3P 1 direct with long terminal shield 14 266 mm

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3.0 cm
Package 1 Width	22.0 cm
Package 1 Length	23.0 cm
Package 1 Weight	780.0 g
Unit Type Of Package 2	S04
Number Of Units In Package 2	25
Package 2 Height	30.0 cm
Package 2 Width	40.0 cm
Package 2 Length	60.0 cm
Package 2 Weight	20.353 kg

Sustainability Screen

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc
Toxic Heavy Metal Free
Mercury Free
Rohs Exemption Information Yes
Halogen Free Plastic Parts Product

Certifications & Standards

Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
	Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile