

Linergy DX 4P distribution block 63A - 4 modules - 24 holes quick connection top

04040

Price: 1,624.52 ZAR

Main

Range	Linergy	
Range Of Product	Prisma Plus System P Prisma Plus System G	
Product Or Component Type	ent Type Distribution block	
Product Name	Linergy DX	
Range Compatibility	Prisma Prisma G Prisma Prisma P Prisma Prisma PH Prisma Pack 160 Prisma Prisma Pack 250	
Product Compatibility	Spacial enclosures	
Ip Degree Of Protection	IPxx B	

Complementary

Location Of Connection	Тор
Mounting Support	DIN rail
Poles Description	4P
[Ue] Rated Operational Voltage	440 V AC
[Ui] Rated Insulation Voltage	500 V AC
[Uimp] Rated Impulse Withstand Voltage	6 kV
[le] Rated Operational Current	63 A at 40 °C
[In] Rated Current	63 A at 40 °C
Connections - Terminals	Supply: tunnel type terminal16 mm² (flexible) Supply: tunnel type terminal25 mm² (rigid) Distribution: spring terminal (phase) , 12 x 2.56 mm² (flexible) Distribution: spring terminal (phase) , 12 x 2.56 mm² (rigid) Distribution: spring terminal (neutral) , 12 x 2.56 mm² (flexible) Distribution: spring terminal (neutral) , 12 x 2.56 mm² (rigid)
9 Mm Pitches	8
Total Number Of 18 Mm Modules	4
Net Weight	0.29 kg

Environment

Pollution Degree	3
Resistance To Incandescent Wire	960 °C conforming to IEC 60695-2-11

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Standards	IEC 60947-7-1
	IEC 61439-2
	IEC 61439-1
Product Certifications	ASEFA

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	7.5 cm
Package 1 Width	7.5 cm
Package 1 Length	10 cm
Package 1 Weight	320 g

Contractual warranty

Warranty 18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Well-being performance

②	Reach Free Of Svhc	
	Toxic Heavy Metal Free	
	Mercury Free	
	Rohs Exemption Information	Yes
Rea	ch Regulation	REACh Declaration
Eu F	Rohs Directive	Compliant
		EU RoHS Declaration
Chir	na Rohs Regulation	China RoHS declaration
		Pro-active China RoHS declaration (out of China RoHS legal scope)
Wee	e	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins