Product datasheet





Galaxy VS UPS 30kW 400V for External Batteries, Start-up 5x8

GVSUPS30KHS

Price: 201,730.50 ZAR

Overview	
Presentation	Highly efficient, easy-to-deploy 30kW, 400V 3-phase uninterruptible power supply (UPS) that brings best-in-class power protection to edge, small and medium data centers, as well as to critical infrastructure in commercial and industrial applications. Compact design, high-density technology and modular architecture keep total cost of ownership low and operational efficiency at the highest levels. Galaxy VS reduces your energy losses by up to 66% with the patented ECOnversion mode – reaching up to 99% efficiency levels and delivering more energy savings than even our industry-leading 97% efficiency in normal operating mode. The UPS is EcoStruxure-ready to give you peace of mind with cloud-based remote monitoring and management via your smartphone. Includes 5x8 start-up service. For battery runtime details, see the runtime charts published under the Documents tab.
Lead Time	Usually Ships within 2 Weeks
Main	
Main Input Voltage	400 V 3 phases
Other Input Voltage	380 V

Main Input Voltage	400 V 3 phases
Other Input Voltage	380 V
	415 V
Main Output Voltage	400 V 3 phases
Other Output Voltage	380 V
	415 V
Rated Power In W	30 kW
Rated Power In Va	30 kVA
Output Connector Type	Hard wire 5-wire (3P + N + E) 1
Battery Type	External battery system
	Li-lon (Lithium-lon)
	VRLA
Provided Equipment	Dust filter
	Installation guide
	Integrated network management
	Power modules ship installed
	a

Batteries & Runtime

Efficiency	View Efficiency Graph ☐
Number Of Battery Filled Slots	0
Number Of Battery Free Slots	0
Battery Voltage	384576 V DC
Discharge Battery Voltage	307 V DC
Max Current Discharge	102 A
Battery Power In Vah	0 VAh runtime

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Start-up service Top and bottom cable entry Extended Runtime 0

General

Bypass Voltage Tolerance	+/- 10 %
Max Bypass Input Current	48 A
Redundant	No

Physical

•	
Colour	White
Height	148.5 cm
Width	52.1 cm
Depth	84.7 cm
Net Weight	206 kg
Usb Compatible	No

Input

Network Frequency	4070 Hz
Number Of Input Connectors	1 hard wire 4-wire (3P + E) 1 hard wire 5-wire (3P + N + E)
Input Voltage Limits	340460 V 400 V
Maximum Input Current	56 A
Max Short Time Withstand Current	65 kA
Input Harmonic Distortion	Less than 3 % for full load
Load Power Factor	From 0.7 leading to 0.7 lagging without any derating
Input Power Factor At Full Load	0.99

Output

Output	
Maximum Configurable Power In W	30 kW
Harmonic Distortion	Less than 3 %
Output Frequency	50 Hz sync to mains 60 Hz sync to mains 60 Hz +/- 0.1 % for 60 Hz nominal unsynchronised 50 Hz +/- 0.1 % for 50 Hz nominal unsynchronised
Crest Factor	2.5
Wave Type	Sine wave
Output Voltage Tolerance	+/-1% after 50ms
Output Harmonic Distortion	< 1% linear load and < 3% non-linear load
Output Overload Operation	10 minutes at 125% and 60 seconds at 150%
Bypass Type	Built-in static bypass
Maximum Configurable Power In Va	30 kVA

Conformance

Standards

CSA C22.2 No 107.3

EN/IEC 62040-1

EN/IEC 62040-2

EN/IEC 62040-3

FCC part 15 class A

IEC 60721-4-2 level 2M2

UL 1778 5th edition

Environmental

Ambient Air Temperature For Operation	040 °C
Relative Humidity	095 % non-condensing
Operating Altitude	03281 ft
Ambient Air Temperature For Storage	-2555 °C
Storage Relative Humidity	1080 % non-condensing
Storage Altitude	0.0015240.00 m
Acoustic Level	65 dBA
Heat Dissipation	2922.4 Btu/h
Ip Degree Of Protection	IP21

Communications & Management

Free Slots	1
Control Panel	Touch screen LCD user interface

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	168 cm
Package 1 Width	99 cm
Package 1 Length	64 cm
Package 1 Weight	235 kg

Contractual warranty

Warranty 1 year on-site repair or replace with factory authorized Start-Up

Sustainability Green Premium*

Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >









Energy Efficient Take-back Transparency RoHS/REACh

Resource performance

Energy

Energy Efficient Product



Take-Back Program Available

Well-being performance



Rohs Exemption Information

Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information