Specification





cam voltmeter switch - 3L - 45° - 12 A - screw mounting

K1D024MLH

Price: 726.03 ZAR

Main

| Range Of Product | Harmony K | |
|--|--|--|
| Product Or Component Type | Complete cam switch | |
| Component Name | K1 | |
| [Ith] Conventional Free Air Thermal Current | 12 A | |
| Mounting Location | Front | |
| Fixing Mode | Multifixing | |
| Cam Switch Head Type | With front plate 45 x 45 mm | |
| Type Of Operator | Black handle, length = 35 mm | |
| Rotary Handle Padlocking | Without | |
| Presentation Of Legend | ation Of Legend With metallic legend, 0 - L1L2 - L2L3 - L3L1 black marking | |
| Cam Switch Function | Function Voltmeter switch | |
| Return | Without | |
| Type Of Measurement | urement Between 3 phases | |
| Off Position | With Off position | |
| Switching Positions | Right: 0° - 45° - 90° - 135° | |
| Ip Degree Of Protection IP40 conforming to IEC 529 | | |

Complementary

| Switching Angle | 45 ° | |
|---|---|--|
| [Ui] Rated Insulation Voltage | 690 V (pollution degree 3) conforming to IEC 60947-1 | |
| [Ithe] Conventional Enclosed Thermal Current | 10 A | |
| Rated Operational Power In W | 10500 W AC-21, 500660 V 3 phases conforming to IEC 947-3 1100 W AC-3, 230 V 3 phases conforming to IEC 947-3 1500 W AC-23A, 230 V 3 phases conforming to IEC 947-3 1500 W AC-3, 400 V 1 phase conforming to IEC 947-3 1500 W AC-3, 400 V 3 phases conforming to IEC 947-3 1500 W AC-3, 500 V 3 phases conforming to IEC 947-3 1500 W AC-3, 690 V 3 phases conforming to IEC 947-3 2200 W AC-23A, 400 V 3 phases conforming to IEC 947-3 2200 W AC-23A, 500 V 3 phases conforming to IEC 947-3 2200 W AC-23A, 690 V 3 phases conforming to IEC 947-3 4800 W AC-21, 230 V 3 phases conforming to IEC 947-3 600 W AC-3, 230 V 1 phase conforming to IEC 947-3 8300 W AC-21, 400 V 3 phases conforming to IEC 947-3 | |

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

| [le] Rated Operational Current Ac | 1.8 A at 690 V AC-3 3 phases conforming to IEC 947-3 2.8 A at 500 V AC-3 3 phases conforming to IEC 947-3 2.8 A at 690 V AC-23A 3 phases conforming to IEC 947-3 3.3 A at 400 V AC-3 3 phases conforming to IEC 947-3 3.8 A at 500 V AC-23A 3 phases conforming to IEC 947-3 4.6 A at 230 V AC-3 3 phases conforming to IEC 947-3 4.8 A at 400 V AC-23A 3 phases conforming to IEC 947-3 5.6 A at 230 V AC-23A 3 phases conforming to IEC 947-3 1 A at 500 V AC-15 conforming to IEC 947-5-1 2 A at 400 V AC-15 conforming to IEC 947-5-1 3 A at 230 V AC-15 conforming to IEC 947-5-1 |
|---|--|
| Electrical Durability | 1000000 cycles AC-15 1000000 cycles AC-21 500000 cycles AC-23 500000 cycles AC-3 |
| Maximum Operating Rate | 2.5 cyc/mn AC-21 2.5 cyc/mn AC-23 2.5 cyc/mn AC-3 8.333 cyc/mn AC-15 |
| Short-Circuit Current | 10000 A |
| Short-Circuit Protection | 16 A cartridge fuse, type gG |
| [Uimp] Rated Impulse Withstand Voltage | 4 kV in isolating function 6 kV conforming to IEC 947-1 |
| Contact Operation | Slow-break |
| Positive Opening | With |
| Electrical Connection | Captive screw clamp terminals flexible, clamping capacity: 2 x 1.5 mm² Captive screw clamp terminals solid, clamping capacity: 1 x 2.5 mm² |
| Mechanical Durability | 1000000 cycles |
| Cad Overall Width | 45 mm |
| Cad Overall Height | 45 mm |
| Cad Overall Depth | 87 mm |
| Net Weight | 0.14 kg |
| Environment | |
| Standards | EN 60947-3 for power circuit EN 60947-5-1 for control circuit CENELEC EN 50013 |
| Product Certifications | CSA 240 V 1 hp 1 phase CSA 240 V 3 hp 3 phases 2 -pole(s) UL 240 V 1 hp 3 phases UL 240 V 0.33 hp 1 phase 2 -pole(s) |
| Protective Treatment | TC |
| Ambient Air Temperature For Operation | -2555 °C |
| Ambient Air Temperature For Storage | -4070 °C |
| Shock Resistance | 30 gn conforming to IEC 68-2-27 |
| Vibration Resistance | 5 gn conforming to IEC 68-2-6 (f = 10150 Hz) |
| Overvoltage Category | Class II conforming to IEC 536 Class II conforming to NF C 20-030 |
| Packing Units | |
| Unit Type Of Package 1 | PCE |
| Number Of Units In Package 1 | 1 |

6.500 cm

Package 1 Height

| Package 1 Width | 6.500 cm |
|------------------------------|-----------|
| Package 1 Length | 11.000 cm |
| Package 1 Weight | 154.800 g |
| Unit Type Of Package 2 | S01 |
| Number Of Units In Package 2 | 10 |
| Package 2 Height | 15.000 cm |
| Package 2 Width | 15.000 cm |
| Package 2 Length | 40.000 cm |
| Package 2 Weight | 1.689 kg |
| Unit Type Of Package 3 | P06 |
| Number Of Units In Package 3 | 320 |
| Package 3 Height | 75.000 cm |
| Package 3 Width | 80.000 cm |
| Package 3 Length | 60.000 cm |
| Package 3 Weight | 62.059 kg |

Contractual warranty

Warranty 18 months

Sustainability Screen Premium

Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

| ⊘ | Reach Free Of Svhc | |
|----------|----------------------------|-----|
| ⊘ | Toxic Heavy Metal Free | |
| ⊘ | Mercury Free | |
| ⊘ | Rohs Exemption Information | Yes |

Certifications & Standards

| Reach Regulation | REACh Declaration |
|--------------------------|---|
| Eu Rohs Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| China Rohs Regulation | China RoHS declaration |
| Environmental Disclosure | Product Environmental Profile |
| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Circularity Profile | No need of specific recycling operations |


24 Apr 2024

K1D024MLH

Dimensions Drawings

Operating Head and Body

Front Mounting "Multi-Fixing"




- a 63 mm/2.48 in.
- e support panel thickness 1 mm to 6 mm./0.039 in. to 0.24 in.

K1D024MLH

Technical Description

Link Positions (Factory Mounted)



Marking




Marking



K1D024MLH

Switching Program



Convention Used for Switching Program Representation

Contact closed

Contact closed in 2 positions and maintained between the 2 positions

Sealed assembly for auto-maintain control

Overlapping contacts

Spring return position: for a switching angle of 90°, spring return is over 30° after the last position (for a maximum of 3 simultaneous contacts).

Example:

