Product datasheet

Specifications





TeSys D reversing contactor -3P(3 NO) - AC-3 - <= 440 V 18 A -110 V AC coil

LC2D18F7

Price: 4,621.35 ZAR

Main

IVIAIII	
Range	TeSys
-	TeSys Deca
Product Name	TeSys D
	TeSys Deca
Product Or Component Type	Reversing contactor
Device Short Name	LC2D
Contactor Application	Resistive load
	Motor control
Utilisation Category	AC-1
	AC-3 AC-3e
Device Presentation	Preassembled with reversing power busbar
Poles Description	
Poles Description	3P
Power Pole Contact Composition	3 NO
[Ue] Rated Operational Voltage	Power circuit: <= 690 V AC 25400 Hz
	Power circuit: <= 300 V DC
[le] Rated Operational Current	18 A (at <60 °C) at <= 440 V AC AC-3 for power circuit
	32 A (at <60 °C) at <= 440 V AC AC-1 for power circuit
	18 A (at <60 °C) at <= 440 V AC AC-3e for power circuit
Motor Power Kw	4 kW at 220230 V AC 5060 Hz
	7.5 kW at 380400 V AC 5060 Hz
	9 kW at 415 V AC 5060 Hz 9 kW at 440 V AC 5060 Hz
	10 kW at 500 V AC 5060 Hz
	10 kW at 660690 V AC 5060 Hz
Motor Power Hp (UI / Csa)	1 hp at 115 V AC 60 Hz for 1 phase motors
	3 hp at 230/240 V AC 60 Hz for 1 phase motors
	5 hp at 200/208 V AC 60 Hz for 3 phases motors
	5 hp at 230/240 V AC 60 Hz for 3 phases motors
	10 hp at 460/480 V AC 60 Hz for 3 phases motors
	15 hp at 575/600 V AC 60 Hz for 3 phases motors
Control Circuit Type	AC at 50/60 Hz
[Uc] Control Circuit Voltage	110 V AC 50/60 Hz
Auxiliary Contact Composition	1 NO + 1 NC
[Uimp] Rated Impulse Withstand Voltage	6 kV conforming to IEC 60947
Overvoltage Category	III
[Ith] Conventional Free Air	10 A (at 60 °C) for signalling circuit
Thermal Current	32 A (at 60 °C) for power circuit
Irms Rated Making Capacity	140 A AC for signalling circuit conforming to IEC 60947-5-1
	250 A DC for signalling circuit conforming to IEC 60947-5-1
	300 A at 440 V for power circuit conforming to IEC 60947

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Rated Breaking Capacity	300 A at 440 V for power circuit conforming to IEC 60947
[Icw] Rated Short-Time Withstand	40 A 40 °C - 10 min for power circuit
Current	84 A 40 °C - 1 min for power circuit
	145 A 40 °C - 10 s for power circuit
	240 A 40 °C - 1 s for power circuit
	100 A - 1 s for signalling circuit
	120 A - 500 ms for signalling circuit
	140 A - 100 ms for signalling circuit
Associated Fuse Rating	10 A gG for signalling circuit conforming to IEC 60947-5-1
	50 A gG at <= 690 V coordination type 1 for power circuit
	35 A gG at <= 690 V coordination type 2 for power circuit
Average Impedance	2.5 mOhm - Ith 32 A 50 Hz for power circuit
[Ui] Rated Insulation Voltage	Power circuit: 690 V conforming to IEC 60947-4-1
	Power circuit: 600 V CSA certified
	Power circuit: 600 V UL certified
	Signalling circuit: 690 V conforming to IEC 60947-1
	Signalling circuit: 600 V CSA certified
	Signalling circuit: 600 V UL certified
Electrical Durability	1.65 Mcycles 18 A AC-3 at Ue <= 440 V
	1 Mcycles 32 A AC-1 at Ue <= 440 V
	1.65 Mcycles 18 A AC-3e at Ue <= 440 V
Power Dissipation Per Pole	0.8 W AC-3
	2.5 W AC-1
	0.8 W AC-3e
Front Cover	With
Interlocking Type	Mechanical
Mounting Support	Plate
	Rail
Standards	CSA C22.2 No 14
	EN 60947-4-1
	EN 60947-5-1
	IEC 60947-4-1
	IEC 60947-5-1
	UL 508
	IEC 60335-1
Product Certifications	DNV
	CSA
	CCC
	UL
	GL
	LROS (Lloyds register of shipping)
	BV
	RINA GOST
	UKCA
Connections - Terminals	Control circuit: screw clamp terminals 1 cable(s) 14 mm ² flexible without cable end
	Control circuit: screw clamp terminals 1 cable(s) 14 mm flexible without cable end Control circuit: screw clamp terminals 2 cable(s) 14 mm²flexible without cable end
	Control circuit: screw clamp terminals 1 cable(s) 14 mm ² flexible with cable end
	Control circuit: screw clamp terminals 2 cable(s) 12.5 mm ² flexible with cable end
	Control circuit: screw clamp terminals 1 cable(s) 14 mm ² solid
	Control circuit: screw clamp terminals 2 cable(s) 14 mm ² solid
	Power circuit: screw clamp terminals 1 cable(s) 1.56 mm ² flexible without cable end
	Power circuit: screw clamp terminals 2 cable(s) 1.56 mm ² flexible without cable end
	Power circuit: screw clamp terminals 1 cable(s) 16 mm ² flexible with cable end
	Power circuit: screw clamp terminals 1 cable(s) 14 mm²flexible with cable end
	Power circuit: screw clamp terminals 1 cable(s) 1.56 mm ² solid
	Power circuit: screw clamp terminals 2 cable(s) 1.56 mm ² solid
Tightening Torque	Power circuit: 1.7 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm
•	Power circuit: 1.7 N.m - on screw clamp terminals - with screwdriver Philips No 2
	Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm
	Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver Philips No 2
	Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver pozidriv No 2
	Power circuit: 2.5 N.m - on screw clamp terminals - with screwdriver pozidriv No 2
Operating Time	1222 ms closing
	419 ms opening

Safety Reliability Level	B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1
Mechanical Durability	15 Mcycles
Maximum Operating Rate	3600 cyc/h 60 °C

Complementary

Coil Technology	Without built-in suppressor module					
Control Circuit Voltage Limits	0.30.6 Uc (-4070 °C):drop-out AC 50/60 Hz 0.81.1 Uc (-4060 °C):operational AC 50 Hz 0.851.1 Uc (-4060 °C):operational AC 60 Hz 11.1 Uc (6070 °C):operational AC 50/60 Hz					
Inrush Power In Va	70 VA 60 Hz cos phi 0.75 (at 20 °C) 70 VA 50 Hz cos phi 0.75 (at 20 °C)					
Hold-In Power Consumption In Va	7.5 VA 60 Hz cos phi 0.3 (at 20 °C) 7 VA 50 Hz cos phi 0.3 (at 20 °C)					
Heat Dissipation	23 W at 50/60 Hz					
Auxiliary Contacts Type	type mechanically linked 1 NO + 1 NC conforming to IEC 60947-5-1 type mirror contact 1 NC conforming to IEC 60947-4-1					
Signalling Circuit Frequency	25400 Hz					
Minimum Switching Current	5 mA for signalling circuit					
Minimum Switching Voltage	17 V for signalling circuit					
Non-Overlap Time	1.5 ms on de-energisation between NC and NO contact 1.5 ms on energisation between NC and NO contact					
Insulation Resistance	> 10 MOhm for signalling circuit					

Environment

Ip Degree Of Protection	P20 front face conforming to IEC 60529			
Climatic Withstand	conforming to IACS E10 conforming to IEC 60947-1 Annex Q category D			
Protective Treatment	TH conforming to IEC 60068-2-30			
Pollution Degree	3			
Ambient Air Temperature For Operation	-4060 °C 6070 °C with derating			
Ambient Air Temperature For Storage	-6080 °C			
Operating Altitude	03000 m			
Fire Resistance	850 °C conforming to IEC 60695-2-1			
Flame Retardance	V1 conforming to UL 94			
Mechanical Robustness	Vibrations contactor open: 2 Gn, 5300 Hz Vibrations contactor closed: 4 Gn, 5300 Hz Shocks contactor open: 10 Gn for 11 ms Shocks contactor closed: 15 Gn for 11 ms			
Height	77 mm			
Width	90 mm			
Depth	86 mm			
Net Weight	0.707 kg			

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	14.000 cm
Package 1 Width	9.500 cm
Package 1 Length	11.300 cm
Package 1 Weight	811.000 g
Unit Type Of Package 2	S02
Number Of Units In Package 2	6
Package 2 Height	15.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	5.256 kg

Contractual warranty

Warranty

18 months

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc
Toxic Heavy Metal Free
Mercury Free
Rohs Exemption Information Yes
Pvc Free


Certifications & Standards


Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information

Product datasheet

Dimensions Drawings

Dimensions





LC2 or 2 x LC1	а	b	c ⁽¹⁾	e1	e2	G
D09 to D18 (AC)	90	77	86	4	1.5	80
D093 to D123 (AC)	90	99	86	-	-	80
D09 to D18 (DC)	90	77	95	4	1.5	80
D093 to D123 (DC)	90	99	95	-	-	80
D25 to D38 (AC)	90	85	92	9	5	80
D183 to D383 (AC)	90	99	92	-	-	80
D25 to D32 (DC)	90	85	101	9	5	80
D183 to D383 (DC)	90	99	101	-	_	80
e1 and e2: including cabling.						
(1) With safety cover, without add-on block.						

Product datasheet

Connections and Schema

Wiring

