## **Product datasheet**

Specifications





# TeSys LE - enclosed DOL starter - 1.2...1.8 A - 230 V AC coil

LE1M35P707

#### Price: 2,954.48 ZAR

#### Main

| Range                                  | TeSys  |
|--|--|
| Product Name                           | TeSys LE   |
| Device Short Name                      | LE1M   |
| Product Or Component Type              | Enclosed DOL starter   |
| Device Application                     | Standard   |
| Utilisation Category                   | AC-3   |
| Device Composition                     | Contactor<br>Earth terminal<br>Neutral terminal<br>Thermal overload relay  |
| Thermal Protection Adjustment<br>Range | 1.21.8 A   |
| Motor Power Kw                         | 0.25 kW at 240 V AC 50/60 Hz<br>0.55 kW at 415 V AC 50/60 Hz<br>0.25 kW at 220/230 V AC 50/60 Hz<br>0.55 kW at 380/400 V AC 50/60 Hz |
| [Uc] Control Circuit Voltage           | 230 V AC 50/60 Hz  |
| Control Type                           | Push-button start green I<br>Push-button stop/reset red O  |

### Complementary

| Local Signalling   | Operating: LED (yellow) |  |
|--------------------|-------------------------|--|
| Cable Entry Number | 2 ISO20 top             |  |
|                    | 2 ISO25 top             |  |
|                    | 2 Pg 13 top             |  |
|                    | 2 Pg 21 top             |  |
|                    | 2 ISO20 bottom          |  |
|                    | 2 ISO25 bottom          |  |
|                    | 2 Pg 13 bottom          |  |
|                    | 2 Pg 21 bottom          |  |
|                    | 2 Pg 16 top             |  |
|                    | 2 Pg 16 bottom          |  |
| Width              | 78 mm                   |  |
| Height             | 160 mm                  |  |
| Depth              | 108 mm                  |  |
| Net Weight 0.6 kg  |                         |  |

### Environment

| Material                | ABS (acrylonitrile butadiene-styrene) |
|-------------------------|---------------------------------------|
| Ip Degree Of Protection | IP65 conforming to IEC 60529          |

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

| Standards                                | IEC 60947-4-1        |
|--|----------------------|
| Ambient Air Temperature For<br>Operation | -540 °C              |
| Environmental Characteristic             | Standard environment |
| Product Certifications                   | UKCA                 |

## **Packing Units**

| Unit Type Of Package 1       | PCE     |
|------------------------------|---------|
| Number Of Units In Package 1 | 1       |
| Package 1 Height             | 11.5 cm |
| Package 1 Width              | 16.5 cm |
| Package 1 Length             | 8.3 cm  |
| Package 1 Weight             | 567.0 g |

## **Contractual warranty**

Warranty

18 months

## Sustainability Screen

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

#### Well-being performance

Reach Free Of Svhc

| Toxic Heavy Metal Free     |     |
|----------------------------|-----|
| Mercury Free               |     |
| Rohs Exemption Information | Yes |

#### **Certifications & Standards**

| Reach Regulation         | REACh Declaration  |
|--------------------------|--|
| Eu Rohs Directive        | Compliant<br>EU RoHS Declaration   |
| China Rohs Regulation    | China RoHS declaration   |
| Environmental Disclosure | Product Environmental Profile  |
| Weee                     | The product must be disposed on European Union markets following specific waste<br>collection and never end up in rubbish bins |
| Circularity Profile      | End of Life Information  |