# **Product datasheet**

Specifications





# switch disconnector ComPact NSX160 NA, 2 poles, 100 A

LV430619

() Discontinued on: 31 Jul 2022

#### Main

Range	ComPact
Product Name	ComPact NSX
Product Or Component Type	Switch disconnector
Device Short Name	Compact NSX160NA
Poles Description	2P
Network Type	AC DC
[Ue] Rated Operational Voltage	690 V AC 50/60 Hz conforming to IEC 60947-3 750 V DC 3 poles in series conforming to IEC 60947-3 500 V DC 2 poles in series conforming to IEC 60947-3 250 V DC 1 pole conforming to IEC 60947-3
[le] Rated Operational Current	AC-22A: 160 A AC 50/60 Hz 220690 V AC-23A: 160 A AC 50/60 Hz 220690 V DC-22A: 160 A DC 250 V 1 pole DC-22A: 160 A DC 500 V 2 poles in series DC-23A: 160 A DC 250 V 1 pole DC-23A: 160 A DC 500 V 2 poles in series
[Ui] Rated Insulation Voltage	800 V AC 50/60 Hz conforming to IEC 60947-3
[Uimp] Rated Impulse Withstand Voltage	8 kV conforming to IEC 60947-3
[Ith] Conventional Free Air Thermal Current	160 A at 60 °C
[Icm] Rated Short-Circuit Making Capacity	330 kA with upstream protection circuit breaker 3.6 kA switch-disconnector alone
Breaking Capacity Code	NA
Suitability For Isolation	Yes conforming to EN 60947-3 Yes conforming to IEC 60947-3
Contact Position Indicator	Yes
Visible Break	No
Pollution Degree	3 conforming to IEC 60664-1

### Complementary

Control Type	Toggle
Mounting Mode	Fixed
Mounting Support	Backplate
Upside Connection	Front
Downside Connection	Front

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

[Icw] Rated Short-Time Withstand	0.96 kA during 20 s conforming to IEC 60947-3
Current	2.5 kA during 1 s conforming to IEC 60947-3
	2.5 kA during 3 s conforming to IEC 60947-3
Mechanical Durability	40000 cycles conforming to IEC 60947-3
Electrical Durability	AC-22A: 10000 cycles 250 V DC In/2 (1 pole) conforming to IEC 60947-3
	AC-22A: 5000 cycles 500 V DC In (2 poles in series) conforming to IEC 60947-3
	AC-23A: 10000 cycles 250 V DC In/2 (1 pole) conforming to IEC 60947-3
	AC-23A: 5000 cycles 500 V DC In (2 poles in series) conforming to IEC 60947-3
	AC-22A: 10000 cycles 690 V AC 50/60 Hz In/2 conforming to IEC 60947-3
	AC-22A: 15000 cycles 440 V AC 50/60 Hz In conforming to IEC 60947-3
	AC-22A: 30000 cycles 440 V AC 50/60 Hz In/2 conforming to IEC 60947-3
	AC-22A: 5000 cycles 690 V AC 50/60 Hz In conforming to IEC 60947-3
	AC-23A: 10000 cycles 690 V AC 50/60 Hz In/2 conforming to IEC 60947-3
	AC-23A: 15000 cycles 440 V AC 50/60 Hz In conforming to IEC 60947-3
	AC-23A: 30000 cycles 440 V AC 50/60 Hz In/2 conforming to IEC 60947-3
	AC-23A: 5000 cycles 690 V AC 50/60 Hz In conforming to IEC 60947-3
Connection Pitch	35 mm
Height	161 mm
Width	105 mm
Depth	86 mm
	1.8 kg

Standards	EN/IEC 60947 UL 508
Product Certifications	EAC CCC
Ip Degree Of Protection	IP40 conforming to IEC 60529
Ik Degree Of Protection	IK07 conforming to IEC 62262
Electrical Shock Protection Class	Class II
Ambient Air Temperature For Operation	-3570 °C
Ambient Air Temperature For Storage	-5585 °C

# **Packing Units**

0	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1

#### **Contractual warranty**

Warranty

18 months

## Sustainability Screen Premium

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



RoHS/REACh

#### Well-being performance

Mercury Free

Rohs Exemption Information Yes

#### **Certifications & Standards**

Eu Rohs Directive	Compliant
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information