Product datasheet

Specification





METSEPM2230 - EasyLogic PM2230. Power & Energy meter. up to 31stH. LCD. RS485. class 0.5S

METSEPM2230

Price: 8,276.95 ZAR

Main

IVIAIII	
Range	EasyLogic
Product Name	EasyLogic PM2200
Device Short Name	PM2230
Product Or Component Type	Power meter

Complementary

Device Application	Power monitoring Sub billing
Power Quality Analysis	total harmonic distortion
	up to the 31st harmonic
Type Of Measurement	Apparent power min/max, total
	Active and reactive power min/max, total
	Current min/max, avg
	Voltage min/max, avg
	Frequency min/max, avg
	Total current harmonic distortion THD (I) per phase
	Total voltage harmonic distortion THD (U) per phase
	Power factor min/max, avg
	Apparent energy total
	Active and reactive energy total
Motoring Type	<u>.</u>
Metering Type	Calculated neutral current
	Active power P, P1, P2, P3
	Current I, I1, I2, I3
	Peak demand power PM, QM, SM
	Voltage U, U21, U32, U13, V, V1, V2, V3
	Peak demand currents
	Reactive power Q, Q1, Q2, Q3
	Demand power P, Q, S
	Unbalance current
	Active, reactive, apparent energy (signed, four quadrant)
	Apparent power S, S1, S2, S3
Accuracy Class	Class 1 reactive energy conforming to IEC 62053-24
	Class 0.5S active energy conforming to IEC 62053-22
	Class 5 harmonic distorsion (I THD & U THD)
Measurement Accuracy	Apparent power +/- 0.5 %
	Active energy +/- 0.5 %
	Reactive energy +/- 1 %
	Active power +/- 0.5 %
	Voltage +/- 0.5 %
	Power factor +/- 0.01
	Current +/- 0.5 %
	Frequency +/- 0.05 %
	56000 mA
Measurement Current	0.110000 1.111
Measurement Current Measurement Voltage	35480 V AC 50/60 Hz between phases

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"



Frequency Measurement Range	4565 Hz
[Us] Rated Supply Voltage	80277 V AC 4565 Hz +/- 10 % 100277 V DC +/- 10 %
Network Frequency	60 Hz 50 Hz
Ride-Through Time	50 ms 120 V AC typical 50 ms 230 V AC typical 50 ms 125 V DC typical
[In] Rated Current	5 A 1 A
Maximum Power Consumption In Va	8 VA at 277 V AC
Maximum Power Consumption In W	3.3 W (power lines (AC)) 3.3 W at 277 V (power lines (DC))
Input Impedance	Current (impedance <= 0.3 mOhm) Voltage (impedance > 5 MOhm)
Tamperproof Of Settings	Protected by access code
Display Type	Backlit LCD
Display Colour	Monochrome
Display Resolution	128 x 128 pixels
Demand Intervals	Configurable from 1 to 60 min
Information Displayed	Demand current (past value) Demand power (past value) Demand power (present value) Voltage Current Frequency Energy consumption Harmonic distortion Power factor Active power Apparent power Reactive power Unbalanced in % Harmonic amplitude
Control Type	4 x button
Local Signalling	Red LED: output signal 19999000 pulse/ k_h (kWh, kVAh, kVARh) Green LED: module operation and integrated communication
Number Of Inputs	0
Number Of Outputs	0
Communication Port Protocol	Modbus RTU at 4800 bps, 9600 bps, 19200 bps, 38.4 Kbps even/odd or none - 2 wires, insulation 2500 V $$
Communication Port Support	Screw terminal block: RS485
Data Recording	Energy consumption logs Power logs Time stamping Min/max for 8 parameters
Function Available	Real time clock
Sampling Rate	64 samples/cycle
Cybersecurity	Enable/disable communication ports
Communication Service	Remote monitoring

Language	Russian French Portuguese English
	Spanish Chinese
	German
Product Certifications	CE conforming to IEC 61010-1 CULus conforming to UL 61010-1 CULus conforming to CSA C22.2 No 61010-1 RCM EAC C-Tick
Mounting Mode	Clip-on
Mounting Position	Vertical
Mounting Support	Framework
Provided Equipment	1 x installation guide
Measurement Category	Category III 480 V Category II 480600 V
Electrical Insulation Class	Double insulation Class II
Flame Retardance	V-0 conforming to UL 94
Connections - Terminals	Current transformer: screw connection (bottom) 6 Voltage inputs: screw connection (top) 4
Material	Polycarbonate
Width	96 mm
Depth	76.09 mm total: 61.64 mm embedded:
Height	96 mm
Net Weight	300 g
Compatibility Code	PM2230
Environment	
Service Life	7 year(s)
Ip Degree Of Protection	IP54 front: conforming to IEC 60529 IP30 body: conforming to IEC 60529
Relative Humidity	595 % at 50 °C
Pollution Degree	2
Ambient Air Temperature For Operation	-1060 °C
Ambient Air Temperature For Storage	-2570 °C
Operating Altitude	<= 2000 m
Electromagnetic Compatibility	Electrostatic discharge conforming to IEC 61000-4-2 Radiated radio-frequency electromagnetic field immunity test conforming to IEC 61000-4-3 Electrical fast transient/burst immunity test conforming to IEC 61000-4-4 Surge immunity test conforming to IEC 61000-4-5 Conducted RF disturbances conforming to IEC 61000-4-6 Magnetic field at power frequency conforming to IEC 61000-4-8 Voltage dips and interruptions immunity test conforming to IEC 61000-4-11 Emission tests conforming to FCC part 15 class A
Overvoltage Category	III

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	11.94 cm
Package 1 Width	12.19 cm
Package 1 Length	8.89 cm
Package 1 Weight	0.37 ka



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information