Specifications





Harmony. Modular timing relay. 8 A. 1 CO. 0.05 s...300 h. dual function. 24...240 V AC/DC

RE22R1AKMR

Price: 1,645.35 ZAR

Main

Range Of Product	Harmony Timer Relays
Product Or Component Type	Dual function relay
Discrete Output Type	Relay
Device Short Name	RE22
Nominal Output Current	8 A

Complementary

oompromontary	
Contacts Type And Composition	1 C/O timed contact, cadmium free
Time Delay Type	Asymmetrical on-delay and off-delay
Time Delay Range	30300 h
	330 min
	30300 s
	0.051 s
	30300 min
	10100 s
	0.33 s
	330 h
	110 s
Control Type	Rotary knob
	Diagnostic button
	Potentiometer external
[Us] Rated Supply Voltage	24240 V AC/DC 50/60 Hz
Release Input Voltage	<= 2.4 V
Voltage Range	0.851.1 Us
Supply Frequency	5060 Hz +/- 5 %
Connections - Terminals	Screw terminals, 1 x 0.51 x 3.3 mm ² (AWG 20AWG 12) solid without cable end Screw terminals, 2 x 0.52 x 2.5 mm ² (AWG 20AWG 14) solid without cable end Screw terminals, 1 x 0.21 x 2.5 mm ² (AWG 24AWG 14) flexible with cable end Screw terminals, 2 x 0.22 x 1.5 mm ² (AWG 24AWG 16) flexible with cable end
Tightening Torque	0.61 N.m conforming to IEC 60947-1
Housing Material	Self-extinguishing
Repeat Accuracy	+/- 0.5 % conforming to IEC 61812-1
Temperature Drift	+/- 0.05 %/°C
Voltage Drift	+/- 0.2 %/V
Setting Accuracy Of Time Delay	+/- 10 % of full scale at 25 °C conforming to IEC 61812-1
Control Signal Pulse Width	100 ms with load in parallel 30 ms
Insulation Resistance	100 MOhm at 500 V DC conforming to IEC 60664-1
	C C

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Recovery Time 120 ms on de-energisation Immunity To Microbreaks 10 ms Power Consumption In Va 3 VA at 240 V AC Power Consumption In W 1.5 W at 240 V DC Switching Capacity In Va 2000 VA Minimum Switching Current 10 mA at 5 V DC Maximum Switching Current 8 A Maximum Switching Voltage 250 V AC Electrical Durability 100000 cycles, 8 A at 250 V, AC-1 Mechanical Durability 1000000 cycles Rated Impulse Withstand Voltage 5 kV for 1.250 µs conforming to IEC 60664-1 Power On Delay 100 ms Creepage Distance 4 kV/3 conforming to IEC 60664-1 Overvoltage Category III conforming to IEC 60664-1 Safety Reliability Data B10d = 18000 MTTFd = 194 years Mounting Position Any position Mounting Support 35 mm DIN rail conforming to IEC 60715 Status Led LED backlight green (steady) for dial pointer indication LED yellow (steady) for output relay energised LED yellow (steat flashing) for timing in progress and output relay energised Width 22.5 mm Net Weight 0.1 kg	
Power Consumption In Va 3 VA at 240 V AC Power Consumption In W 1.5 W at 240 V DC Switching Capacity In Va 2000 VA Minimum Switching Current 10 mA at 5 V DC Maximum Switching Current 8 A Maximum Switching Voltage 250 V AC Electrical Durability 100000 cycles, 8 A at 250 V, AC-1 100000 cycles, 2 A at 24 V, DC-1 Mechanical Durability 1000000 cycles Rated Impulse Withstand Voltage 5 kV for 1.250 µs conforming to IEC 60664-1 Power On Delay 100 ms Creepage Distance 4 kV/3 conforming to IEC 60664-1 Overvoltage Category III conforming to IEC 60664-1 Safety Reliability Data B10d = 180000 MTTFd = 194 years Mounting Position Any position Mounting Support 35 mm DIN rail conforming to IEC 60715 Status Led LED backlight green (steady) for dial pointer indication LED yellow (steady) for output relay energised LED yellow (steady) for timing in progress and output relay energised LED yellow (steady) for timing in progress and output relay energised LED yellow (steady) for timing in progress and output relay energised Width 22.5 mm	
Power Consumption In W 1.5 W at 240 V DC Switching Capacity In Va 2000 VA Minimum Switching Current 10 mA at 5 V DC Maximum Switching Current 8 A Maximum Switching Voltage 250 V AC Electrical Durability 100000 cycles, 8 A at 250 V, AC-1 100000 cycles, 2 A at 24 V, DC-1 Mechanical Durability 1000000 cycles Rated Impulse Withstand Voltage 5 kV for 1.250 µs conforming to IEC 60664-1 Power On Delay 100 ms Creepage Distance 4 kV/3 conforming to IEC 60664-1 Overvoltage Category III conforming to IEC 60664-1 Safety Reliability Data B10d = 180000 MTTFd = 194 years Mounting Position Any position Mounting Support 35 mm DIN rail conforming to IEC 60715 Status Led LED backlight green (steady) for dial pointer indication LED yellow (steady) for output relay energised LED yellow (steady) for timing in progress and output relay energised LED yellow (steady) for timing in progress and output relay energised LED yellow (steady) for timing in progress and output relay energised LED yellow (steady) for timing in progress and output relay energised LED yellow (steady) for timing in progress and output relay energised LED yellow (steady) for timing in progress and output relay energised </th <th></th>	
Switching Capacity In Va 2000 VA Minimum Switching Current 10 mA at 5 V DC Maximum Switching Current 8 A Maximum Switching Voltage 250 V AC Electrical Durability 100000 cycles, 8 A at 250 V, AC-1 100000 cycles, 2 A at 24 V, DC-1 Mechanical Durability 10000000 cycles Rated Impulse Withstand Voltage 5 kV for 1.250 µs conforming to IEC 60664-1 Power On Delay 100 ms Creepage Distance 4 kV/3 conforming to IEC 60664-1 Overvoltage Category III conforming to IEC 60664-1 Safety Reliability Data B10d = 180000 MTTFd = 194 years Mounting Position Any position Mounting Support 35 mm DIN rail conforming to IEC 60715 Status Led LED backlight green (steady) for dial pointer indication LED yellow (steady) for timing in progress and output relay energised LED yellow (steady) for timing in progress and output relay energised Vidth 22.5 mm	
Minimum Switching Current 10 mA at 5 V DC Maximum Switching Current 8 A Maximum Switching Voltage 250 V AC Electrical Durability 100000 cycles, 8 A at 250 V, AC-1 1000000 cycles, 2 A at 24 V, DC-1 Mechanical Durability 10000000 cycles Rated Impulse Withstand Voltage 5 kV for 1.250 µs conforming to IEC 60664-1 Power On Delay 100 ms Creepage Distance 4 kV/3 conforming to IEC 60664-1 Overvoltage Category III conforming to IEC 60664-1 Safety Reliability Data B10d = 180000 MTTFd = 194 years Mounting Position Any position Mounting Support 35 mm DIN rail conforming to IEC 60715 Status Led LED backlight green (steady) for dial pointer indication LED yellow (steady) for output relay energised LED yellow (steady) for timing in progress and output relay de-energised LED yellow (slow flashing) for timing in progress and output relay energised UP yellow (slow flashing) for timing in progress and output relay energised UED yellow (slow flashing) for timing in progress and output relay energised UP yellow (slow flashing) for timing in progress and output relay energised UED yellow (slow flashing) for timing in progress and output relay energised UED yellow (slow flashing) for timing in progress and output relay energised <th></th>	
Maximum Switching Current 8 A Maximum Switching Voltage 250 V AC Electrical Durability 100000 cycles, 8 A at 250 V, AC-1 100000 cycles, 2 A at 24 V, DC-1 Mechanical Durability 1000000 cycles Rated Impulse Withstand Voltage 5 kV for 1.250 µs conforming to IEC 60664-1 Power On Delay 100 ms Creepage Distance 4 kV/3 conforming to IEC 60664-1 Overvoltage Category III conforming to IEC 60664-1 Safety Reliability Data B10d = 180000 MTTFd = 194 years Mounting Position Any position Mounting Support 35 mm DIN rail conforming to IEC 60715 Status Led LED backlight green (steady) for dial pointer indication LED yellow (steady) for output relay energised LED yellow (steady) for timing in progress and output relay de-energis LED yellow (steat flashing) for timing in progress and output relay de-energis LED yellow (steat flashing) for timing in progress and output relay energised LED yellow (steat flashing) for timing in progress and output relay energised LED yellow (steat flashing) for timing in progress and output relay energised LED yellow (steat flashing) for timing in progress and output relay energised LED yellow (steat flashing) for timing in progress and output relay energised LED yellow (steat flashing) for timing in progress and output relay energised LED yellow (steat flashing) for timing in progress and output relay energised	
Maximum Switching Voltage 250 V AC Electrical Durability 100000 cycles, 8 A at 250 V, AC-1 1000000 cycles, 2 A at 24 V, DC-1 Mechanical Durability 10000000 cycles Rated Impulse Withstand Voltage 5 kV for 1.250 µs conforming to IEC 60664-1 Power On Delay 100 ms Creepage Distance 4 kV/3 conforming to IEC 60664-1 Overvoltage Category III conforming to IEC 60664-1 Safety Reliability Data B10d = 180000 MTTFd = 194 years Mounting Position Any position Mounting Support 35 mm DIN rail conforming to IEC 60715 Status Led LED backlight green (steady) for dial pointer indication LED yellow (steady) for cutput relay energised LED yellow (stow flashing) for timing in progress and output relay de-energised LED yellow (stow flashing) for timing in progress and output relay energised Width 22.5 mm	
Electrical Durability 100000 cycles, 8 A at 250 V, AC-1 100000 cycles, 2 A at 24 V, DC-1 Mechanical Durability 1000000 cycles Rated Impulse Withstand Voltage 5 kV for 1.250 µs conforming to IEC 60664-1 Power On Delay 100 ms Creepage Distance 4 kV/3 conforming to IEC 60664-1 Overvoltage Category III conforming to IEC 60664-1 Safety Reliability Data B10d = 180000 MTTFd = 194 years Mounting Position Any position Mounting Support 35 mm DIN rail conforming to IEC 60715 Status Led LED backlight green (steady) for dial pointer indication LED yellow (steady) for output relay energised LED yellow (steat flashing) for timing in progress and output relay de-energise LED yellow (steat flashing) for timing in progress and output relay energised Width 22.5 mm	
100000 cycles, 2 A at 24 V, DC-1 Mechanical Durability 1000000 cycles Rated Impulse Withstand Voltage 5 kV for 1.250 μs conforming to IEC 60664-1 Power On Delay 100 ms Creepage Distance 4 kV/3 conforming to IEC 60664-1 Overvoltage Category III conforming to IEC 60664-1 Safety Reliability Data B10d = 180000 MTTFd = 194 years Mounting Position Any position Mounting Support 35 mm DIN rail conforming to IEC 60715 Status Led LED backlight green (steady) for dial pointer indication LED yellow (steady) for output relay energised LED yellow (steady) for timing in progress and output relay de-energis LED yellow (slow flashing) for timing in progress and output relay energised Width 22.5 mm	
Rated Impulse Withstand Voltage 5 kV for 1.250 µs conforming to IEC 60664-1 Power On Delay 100 ms Creepage Distance 4 kV/3 conforming to IEC 60664-1 Overvoltage Category III conforming to IEC 60664-1 Safety Reliability Data B10d = 180000 MTTFd = 194 years Mounting Position Any position Mounting Support 35 mm DIN rail conforming to IEC 60715 Status Led LED backlight green (steady) for dial pointer indication LED yellow (steady) for output relay energised LED yellow (steat flashing) for timing in progress and output relay de-energised LED yellow (steat flashing) for timing in progress and output relay energised Width 22.5 mm	
Power On Delay 100 ms Creepage Distance 4 kV/3 conforming to IEC 60664-1 Overvoltage Category III conforming to IEC 60664-1 Safety Reliability Data B10d = 180000 MTTFd = 194 years Mounting Position Any position Mounting Support 35 mm DIN rail conforming to IEC 60715 Status Led LED backlight green (steady) for dial pointer indication LED yellow (steady) for output relay energised LED yellow (steady) for timing in progress and output relay de-energise LED yellow (steating) for timing in progress and output relay energised Width 22.5 mm	
Creepage Distance 4 kV/3 conforming to IEC 60664-1 Overvoltage Category III conforming to IEC 60664-1 Safety Reliability Data B10d = 180000 MTTFd = 194 years Mounting Position Any position Mounting Support 35 mm DIN rail conforming to IEC 60715 Status Led LED backlight green (steady) for dial pointer indication LED yellow (steady) for output relay energised LED yellow (slow flashing) for timing in progress and output relay energised Width 22.5 mm	
Overvoltage Category III conforming to IEC 60664-1 Safety Reliability Data B10d = 180000 MTTFd = 194 years Mounting Position Any position Mounting Support 35 mm DIN rail conforming to IEC 60715 Status Led LED backlight green (steady) for dial pointer indication LED yellow (steady) for output relay energised LED yellow (steady) for timing in progress and output relay de-energised LED yellow (slow flashing) for timing in progress and output relay energised Width 22.5 mm	
Safety Reliability Data B10d = 180000 MTTFd = 194 years Mounting Position Any position Mounting Support 35 mm DIN rail conforming to IEC 60715 Status Led LED backlight green (steady) for dial pointer indication LED yellow (steady) for output relay energised LED yellow (fast flashing) for timing in progress and output relay de-energised LED yellow (slow flashing) for timing in progress and output relay energised Width 22.5 mm	
MTTFd = 194 years Mounting Position Any position Mounting Support 35 mm DIN rail conforming to IEC 60715 Status Led LED backlight green (steady) for dial pointer indication LED yellow (steady) for output relay energised LED yellow (fast flashing) for timing in progress and output relay de-energise LED yellow (slow flashing) for timing in progress and output relay energised Width 22.5 mm	
Mounting Support 35 mm DIN rail conforming to IEC 60715 Status Led LED backlight green (steady) for dial pointer indication LED yellow (steady) for output relay energised LED yellow (fast flashing) for timing in progress and output relay de-energise LED yellow (slow flashing) for timing in progress and output relay energised Width 22.5 mm	
Status Led LED backlight green (steady) for dial pointer indication LED yellow (steady) for output relay energised LED yellow (fast flashing) for timing in progress and output relay de-energise Width 22.5 mm	
Width 22.5 mm	
Net Weight 0.1 kg	
Number Of Functions 2	

Environment

Dielectric Strength 2.5 kV for 1 mA/1 minute at 50 Hz between relay output and power insulation conforming to IEC 61812-1 Standards UL 508 IEC 61812-1 Directives 2006/95/EC - low voltage directive 2004/108/EC - electromagnetic compatibility Product Certifications EAC CSA UL	
Directives 2006/95/EC - low voltage directive 2004/108/EC - electromagnetic compatibility Product Certifications EAC CSA	er supply with basic
Product Certifications EAC CSA	
CSA	
RCM CCC GL CE	
Ambient Air Temperature For -2060 °C Operation	
Ambient Air Temperature For -40…70 °C Storage	
Ip Degree Of Protection IP40 housing: conforming to IEC 60529 IP50 front face: conforming to IEC 60529 IP20 terminals: conforming to IEC 60529	
Pollution Degree 3 conforming to IEC 60664-1	
Vibration Resistance 20 m/s² (f= 10150 Hz) conforming to IEC 60068-2-6	

Shock Resistance	15 gn not operating for 11 ms conforming to IEC 60068-2-27 5 gn in operation for 11 ms conforming to IEC 60068-2-27
Relative Humidity	95 % at 2555 °C
Electromagnetic Compatibility	Fast transients immunity test - test level: 1 kV level 3 (capacitive connecting clip) conforming to IEC 61000-4-4 Surge immunity test - test level: 1 kV level 3 (differential mode) conforming to IEC
	61000-4-5
	Surge immunity test - test level: 2 kV level 3 (common mode) conforming to IEC 61000-4-5
	Electrostatic discharge - test level: 6 kV level 3 (contact discharge) conforming to IEC 61000-4-2
	Electrostatic discharge - test level: 8 kV level 3 (air discharge) conforming to IEC 61000-4-2
	Radiated radio-frequency electromagnetic field immunity test - test level: 10 V/m level 3 (80 MHz1 GHz) conforming to IEC 61000-4-3
	Conducted RF disturbances - test level: 10 V level 3 (0.1580 MHz) conforming to IEC 61000-4-6
	Fast transient bursts - test level: 2 kV level 3 (direct contact) conforming to IEC 61000-4-4
	Immunity to microbreaks and voltage drops - test level: 30 % (500 ms) conforming to IEC 61000-4-11
	Immunity to microbreaks and voltage drops - test level: 100 % (20 ms) conforming to IEC 61000-4-11

Packing Units

PCE
1
8.64 cm
9.91 cm
2.79 cm
0.1 kg
S02
40
15 cm
30 cm
40 cm
4.691 kg
P06
640
50 cm
80 cm
60 cm

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance




Rohs Exemption Information
 Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information


Dimensions Drawings

Dimensions



Connections and Schema

Wiring Diagram



RE22R1AKMR


Technical Description

Function Ak: Asymmetrical On-Delay & Off-Delay with Control Signal

Description

After energisation of power supply and energization of Y1, timing starts for a period Ta.At the end of this timing period Ta, the output(s) R closes.Deenergization of Y1 causes a second timing period Tr to start.At the end of this timing period Tr, the output(s) R reverts to its initial state.

Function: 1 Output




RE22R1AKMR

Function Akt: Asymmetrical On-Delay & Off-Delay with Control Signal & with Pause / Summation Control

Description

After energisation of power supply and energization of Y1, timing starts for a period Ta.At the end of this timing period Ta, the output(s) R closes.Deenergization of Y1 causes a second timing period Tr to start.At the end of this timing period Tr, the output(s) R reverts to its initial state.

Function: 1 Output



Ta = t1 + t2 +... Tr = t'1 + t'2 +...

Legend

	Relay de-energised	
	Relay energised	
	Output open	
	Output closed	
U -	Supply	
R1 -	Timed output	
Ta -	Adjustable On-delay	
Tr -	Adjustable Off-delay	
X1 -	Pause / Summation control	
Y1 -	Retrigger / Restart control	