## **Product datasheet**

Specification





# TeSys VARIO - Switch body for switch-disconnector - 3 poles - 63 A

V

Price: 1,164.15 ZAR

### Main

| Range             | TeSys       |
|-------------------|-------------|
| Product Name      | TeSys VARIO |
| Device Short Name | V           |
| Product Type      | Switch body |

### **Complementary**

| Complementary                                   |  |
|---|--|
| Mounting Support                                | Plate                                    |
| 3 - 4,  | Symmetrical rail                         |
|   |  |
| Performance Level                               | High performance                         |
| Number Of Poles                                 | 3P                                       |
|   |  |
| Contact Type And Composition                    | 3 NO                                     |
| Network Type                                    | DC                                       |
|   | AC                                       |
| Network Frequency                               | 50/60 Hz                                 |
| [Ue] lec Rated Operational<br>Voltage           | 690 V AC 50/60 Hz                        |
| lec Rated Operational Power In W                | 11 kW at 230240 V (AC-3)                 |
|   | 22 kW at 500 V (AC-3)                    |
|   | 22 kW at 690 V (AC-23A)                  |
|   | 30 kW at 500 V (AC-23A)                  |
|   | 18.5 kW at 400415 V (AC-3)               |
|   | 18.5 kW at 690 V (AC-3)                  |
|   | 15 kW at 230240 V (AC-23A)               |
|   | 22 kW at 400415 V (AC-23A)               |
| [le] Rated Operational Current                  | 41.5 A AC-23 Ue: 400 V                   |
| [Ith] Conventional Free Air<br>Thermal Current  | 63 A                                     |
| [Ithe] Conventional Enclosed<br>Thermal Current | 50 A                                     |
| Making Capacity ( I Rms)                        | 630 A at 400 V AC-21A                    |
|   | 630 A at 400 V AC-22A                    |
|   | 630 A at 400 V AC-23A                    |
| Breaking Capacity                               | 500 A at 400 V (AC-21A)                  |
|   | 500 A at 400 V (AC-22A)                  |
|   | 500 A at 400 V (AC-23A)                  |
| Rated Conditional Short Circuit                 | 10 kA at 400 V - associated fuse 63 A aM |
| Current   | 10 kA at 400 V - associated fuse 63 A gG |
| [Icm] Rated Short Circuit Making Capacity       | 2.1 kA at 400 V at Ipeak                 |
| Intermittent Duty Class                         | 30                                       |
| Suitability For Isolation                       | Yes                                      |

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

| [Uimp] Rated Impulse Withstand Voltage       | 8 kV  |
|--|---|
| [Icw] Rated Short-Time Withstand Rms Current | 756 A at 400 V duration: 1 s  |
| Mechanical Durability                        | 30000 cycles  |
| Electrical Durability                        | 30000 cycles AC-21<br>30000 cycles DC-15  |
| lec Terminal Connection                      | Power circuit: screw clamp terminals16 mm² - flexible - with cable end Power circuit: screw clamp terminals25 mm² - solid |
| Tightening Torque                            | Power circuit: 4 N.m - on screw clamp terminals   |
| Height                                       | 83 mm   |
| Width  | 60 mm   |
| Depth  | 65 mm   |
| Product Weight                               | 0.5 kg  |

## **Environment**

| Standards                             | IEC 60947-3   |
|---------------------------------------|---|
| Product Certifications                | UL<br>CSA<br>GL<br>UKCA   |
| Degree Of Protection                  | IP20 conforming to IEC 60529  |
| Protective Treatment                  | тс  |
| Mechanical Robustness                 | Vibrations 10150 Hz (1 gn) conforming to IEC 60068-2-6<br>Shocks 11 ms (30 Gn) conforming to IEC 60068-2-27 |
| Ambient Air Temperature For Operation | -2050 °C  |
| Fire Resistance                       | 960 °C conforming to IEC 60695-2-1  |

## **Packing Units**

| PCE       |
|-----------|
|           |
| 1         |
| 11.500 cm |
| 8.500 cm  |
| 8.000 cm  |
| 302.000 g |
| S02       |
| 12        |
| 15.000 cm |
| 30.000 cm |
| 40.000 cm |
| 3.968 kg  |
| P06       |
| 192       |
| 75.000 cm |
| 60.000 cm |
| 80.000 cm |
|           |

Package 3 Weight 71.460 kg

## **Contractual warranty**

Warranty 18 months

## Sustainability Green Premium\*

**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

### Well-being performance

| <b>⊘</b> | Toxic Heavy Metal Free         |
|----------|--------------------------------|
| <b>⊘</b> | Mercury Free                   |
| <b>⊘</b> | Rohs Exemption Information Yes |
| <b>⊘</b> | Pvc Free                       |
| <b>⊘</b> | Halogen Free Product           |

#### **Certifications & Standards**

| Reach Regulation         | REACh Declaration   |
|--------------------------|---|
| Eu Rohs Directive        | Compliant with Exemptions   |
| China Rohs Regulation    | China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information                         |
| Environmental Disclosure | Product Environmental Profile   |
| Weee                     | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Circularity Profile      | No need of specific recycling operations  |