# **Product datasheet**

Specifications





# TeSys Vario - emergency stop switch disconnector - 12 A - on door

VCD02

### Price: 763.76 ZAR

#### Main

| Range             | TeSys                              |
|-------------------|------------------------------------|
| Product Name      | TeSys VARIO                        |
| Device Short Name | VCD                                |
| Product Type      | Emergency stop switch disconnector |

# Complementary

| oomplemental y                                  |  |
|---|--|
| Device Composition                              | Switch<br>Handle   |
| Mounting Support                                | Handle: door<br>Switch: door   |
| Mounting Method                                 | Hole with 22.5 mm for handle   |
| Performance Level                               | High performance   |
| Number Of Poles                                 | 3P   |
| Contact Type And Composition                    | 3 NO   |
| [Ue] lec Rated Operational<br>Voltage           | 690 V AC 50/60 Hz  |
| lec Rated Operational Power In W                | 3 kW at 400415 V (AC-3)<br>4 kW at 500 V (AC-3)<br>1.5 kW at 230240 V (AC-3)<br>5.5 kW at 500 V (AC-23A)<br>5.5 kW at 690 V (AC-3)<br>7.5 kW at 690 V (AC-23A)<br>3 kW at 230240 V (AC-23A)<br>4 kW at 400415 V (AC-23A) |
| [Ie] Rated Operational Current                  | 8.1 A AC-23 Ue: 400 V  |
| [Ith] Conventional Free Air<br>Thermal Current  | 12 A   |
| [Ithe] Conventional Enclosed<br>Thermal Current | 10 A   |
| Making Capacity ( I Rms)                        | 120 A at 400 V AC-21A<br>120 A at 400 V AC-22A<br>120 A at 400 V AC-23A  |
| Breaking Capacity                               | 120 A at 400 V (AC-21A)<br>120 A at 400 V (AC-22A)<br>120 A at 400 V (AC-23A)  |
| Rated Conditional Short Circuit<br>Current      | 10 kA at 400 V - associated fuse 12 A aM<br>10 kA at 400 V - associated fuse 12 A gG   |
| [Icm] Rated Short Circuit Making<br>Capacity    | 1 kA at 400 V at Ipeak   |
| [Icw] Rated Short Time Withstand<br>Current     | 300 A at 400 V duration: 1 s   |
| [Uimp] Rated Impulse Withstand<br>Voltage       | 8 kV   |

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

| Suitability For Isolation    | Yes   |
|------------------------------|---|
|                              | 100   |
| Network Type                 | DC  |
|                              | AC  |
| Intermittent Duty Class      | 30  |
| Control Type                 | Rotary handle   |
| Rotary Handle Mounting Style | Direct  |
| Handle Color                 | Red   |
| Handle Front Plate Color     | Yellow  |
| Rotary Handle Padlocking     | 1 to 3 padlocks 48 mm   |
| Marking                      | 0 - 1   |
| Mechanical Durability        | 100000 cycles   |
| Electrical Durability        | 100000 cycles AC-21   |
|                              | 30000 cycles DC-1   |
|                              | 30000 cycles DC-2   |
|                              | 30000 cycles DC-3   |
|                              | 30000 cycles DC-4   |
|                              | 30000 cycles DC-5   |
| lec Terminal Connection      | Power circuit: screw clamp terminals10 mm <sup>2</sup> - solid                    |
|                              | Power circuit: screw clamp terminals6 mm <sup>2</sup> - flexible - with cable end |
| Tightening Torque            | Power circuit: 2.1 N.m - on screw clamp terminals                                 |
| Base Dimension               | 60 x 60 mm  |
| Height                       | 74 mm   |
| Width                        | 60 mm   |
| Product Weight               | 0.215 kg  |

# Environment

| Standards                                | IEC 60947-3   |
|--|---|
| Product Certifications                   | CSA<br>UL<br>GL<br>CCC<br>UKCA  |
| Degree Of Protection                     | IP20 conforming to IEC 60529<br>IP65  |
| Protective Treatment                     | TC  |
| Mechanical Robustness                    | Vibrations 10150 Hz (1 gn) conforming to IEC 60068-2-6<br>Shocks 11 ms (30 Gn) conforming to IEC 60068-2-27 |
| Ambient Air Temperature For<br>Operation | -2050 °C  |
| Fire Resistance                          | 960 °C conforming to IEC 60695-2-1  |
| Compatibility Code                       | Main switch disconnector  |

# **Packing Units**

| <del></del>                  |         |
|------------------------------|---------|
| Unit Type Of Package 1       | PCE     |
| Number Of Units In Package 1 | 1       |
| Package 1 Height             | 7.8 cm  |
| Package 1 Width              | 8.5 cm  |
| Package 1 Length             | 12.0 cm |

| Package 1 Weight             | 221.0 g  |
|------------------------------|----------|
| Unit Type Of Package 2       | S03      |
| Number Of Units In Package 2 | 24       |
| Package 2 Height             | 30.0 cm  |
| Package 2 Width              | 30.0 cm  |
| Package 2 Length             | 40.0 cm  |
| Package 2 Weight             | 5.795 kg |

# **Contractual warranty**

Warranty

18 months

# Sustainability Screen

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

### Well-being performance

| Mercury Free               |     |
|----------------------------|-----|
| Rohs Exemption Information | Yes |
| Pvc Free                   |     |
| Halogen Free Product       |     |

### **Certifications & Standards**

| Reach Regulation         | REACh Declaration   |
|--------------------------|---|
| Eu Rohs Directive        | Compliant with Exemptions   |
| China Rohs Regulation    | China RoHS declaration<br>Product out of China RoHS scope. Substance declaration for your information                       |
| Environmental Disclosure | Product Environmental Profile   |
| Weee                     | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Circularity Profile      | No need of specific recycling operations  |